


Proton • Area Light • Elements Series



Pre-Lamped Fixtures

- PR12-L127-BZ (Proton12, 12V, LED, 1W, 2700K, bronze)
- PR12-L127-BK (Proton12, 12V, LED, 1W, 2700K, black)
- PR12-L227-BZ (Proton12, 12V, LED, 2W, 2700K, bronze)
- PR12-L227-BK (Proton12, 12V, LED, 2W, 2700K, black)
- PR18-L127-BZ (Proton18, 12V, LED, 1W, 2700K, bronze)
- PR18-L127-BK (Proton18, 12V, LED, 1W, 2700K, black)
- PR18-L227-BZ (Proton18, 12V, LED, 2W, 2700K, bronze)
- PR18-L227-BK (Proton18, 12V, LED, 2W, 2700K, black)

Non-Lamped Fixtures

- PR12-NL-BZ (Proton12, no lamp, bronze)
- PR12-NL-BK (Proton12, no lamp, black)
- PR18-NL-BZ (Proton18, no lamp, bronze)
- PR18-NL-BK (Proton18, no lamp, black)



Area Light



Light Level



UL 2108:2004 R12.07
CSA C22.2.9.0-96 (R2006)

Specifications & Features

- Marine grade A360 alloy construction
- Borosilicate glass lens
- 1' FLEX™ Auxiliary wire lead
- 15' direct burial cable
- AMC - Anti-Moisture Connections
- White reflection panel under shroud for greater luminence
- Available in 12" and 18" stem lengths
- 2W max. LED lamp / 20W max. halogen
- Large composite stake with brass threaded insert
- Limited 10 year warranty



Dimensions

Height: PR12= 15" Overall height (381 mm)
PR18= 21" Overall height (533.4 mm)
Diameter: 5" (127 mm)

Ideal Uses

Area lighting
Pathway lighting
Ambiance

Neutron • Area Light • Elements Series



Pre-Lamped Fixtures

- NU12-L127-BZ (Neutron12, 12V, LED, 1W, 2700K, bronze)
- NU12-L127-BK (Neutron12, 12V, LED, 1W, 2700K, black)
- NU12-L227-BZ (Neutron12, 12V, LED, 2W, 2700K, bronze)
- NU12-L227-BK (Neutron12, 12V, LED, 2W, 2700K, black)
- NU18-L127-BZ (Neutron18, 12V, LED, 1W, 2700K, bronze)
- NU18-L127-BK (Neutron18, 12V, LED, 1W, 2700K, black)
- NU18-L227-BZ (Neutron18, 12V, LED, 2W, 2700K, bronze)
- NU18-L227-BK (Neutron18, 12V, LED, 2W, 2700K, black)

Non-Lamped Fixtures

- NU12-NL-BZ (Neutron12, no lamp, bronze)
- NU12-NL-BK (Neutron12, no lamp, black)
- NU18-NL-BZ (Neutron18, no lamp, bronze)
- NU18-NL-BK (Neutron18, no lamp, black)



Area Light



Light Level



UL 2108:2004 R12.07
CSA C22.2.9.0-96 (R2006)

Specifications & Features

- Marine grade A360 alloy construction
- Borosilicate glass lens
- 1' FLEX™ Auxiliary wire lead
- 15' direct burial cable
- AMC - Anti-Moisture Connections
- White reflection panel under shroud for greater luminence
- Available in 12" and 18" stem lengths
- 2W max. LED lamp / 20W max. halogen
- Large composite stake with brass threaded insert
- Limited 10 year warranty

Dimensions

Height: NU12= 15" Overall height (381 mm)
NU18= 21" Overall height (533.4 mm)
Diameter: 7" (177.8 mm)

Ideal Uses

Area lighting
Pathway lighting
Ambiance

Powder Coated Finishes

N/A