


Positron • Up Light • Elements Series



Standard Finish
WB - Weathered Brass

Pre-Lamped Fixtures

POSI-L427-WB (Positron, shrouded, 12V, LED, 4W, 2700K, WB)
POSI-L430-WB (Positron, shrouded, 12V, LED, 4W, 3000K, WB)

Non-Lamped Fixtures

N/A



Up Light



Light Level



UL 2108:2004 R12.07
CSA C22.2.9.0-96 (R2006)

Specifications & Features

- Brass die-cast body
- High temperature silicone o-rings
- AMC - Anti-Moisture Connections
- FLEX GOLD™ Series LED E-4 watt lamp included
- 8W max. LED lamp / 35W max. halogen
- 1' FLEX™ Auxiliary wire lead
- 15' direct burial cable
- Composite stake with brass threaded insert
- Product ships lamped and staked (Ready to install)
- Limited 10 year warranty

Dimensions

Height: 6.75" (171.45 mm)
Diameter: 2.5" (63.5 mm)

Ideal Uses

- Up lighting
- Graze lighting
- Tall structures

Nucleus • Up Light • Elements Series



Non-shrouded version available



Optional Finish
BZ - Bronze



Optional Finish
BK - Black

Pre-Lamped Fixtures

NUCS-L427-BZ (Nucleus, shrouded, 12V, LED, 4W, 2700K, BZ)
NUCS-L427-BK (Nucleus, shrouded, 12V, LED, 4W, 2700K, BK)
NUCL-L427-BZ (Nucleus, no shroud, 12V, LED, 4W, 2700K, BZ)
NUCL-L427-BK (Nucleus, no shroud, 12V, LED, 4W, 2700K, BK)

Non-Lamped Fixtures

NUCS-NL-BZ (Nucleus, shrouded, no lamp, BZ)
NUCS-NL-BK (Nucleus, shrouded, no lamp, BK)
NUCL-NL-BZ (Nucleus, non-shrouded, no lamp, BZ)
NUCL-NL-BK (Nucleus, non-shrouded, no lamp, BK)



Up Light



Light Level



UL 2108:2004 R12.07
CSA C22.2.9.0-96 (R2006)

Specifications & Features

- Marine grade A360 alloy construction
- High temperature silicone o-rings
- AMC - Anti-Moisture Connections
- Available in shrouded and non-shrouded version
- 8W max. LED lamp / 35W max. halogen
- 1' FLEX™ Auxiliary wire lead
- 15' direct burial cable
- Composite stake with brass threaded insert
- Limited 10 year warranty

Dimensions

Height: 8.75" (222.25 mm)
Diameter: 2.5" (63.5 mm)

Ideal Uses

- Up lighting
- Graze lighting
- Tall structures

Powder Coated Finishes

N/A