



**4245** Aluminum | 20 W max (2) (halogen) | T3 Lamp (2) or LED | LN-10 T3 Std



**4246** Aluminum | 20 W max (2) (halogen) | T3 Lamp (2) or LED | LN-10 T3 Std



	HOUSING/MOUNTING	LENS
<b>4241</b>	<ul style="list-style-type: none"> <li>» Copper-free aluminum</li> <li>» Stamped and formed</li> <li>» 1/2" knockouts on back and side</li> </ul>	<ul style="list-style-type: none"> <li>» Translucent</li> <li>» Molded</li> <li>» High-impact</li> <li>» Polycarbonate</li> </ul>
<b>4242</b>	<ul style="list-style-type: none"> <li>» Recessed mounting box</li> </ul>	<ul style="list-style-type: none"> <li>» Clear</li> <li>» High-impact</li> <li>» Polycarbonate</li> </ul>
<b>4243</b>	<ul style="list-style-type: none"> <li>» Die-cast</li> <li>» Copper-free aluminum</li> <li>» Surface mounting plate</li> </ul>	<ul style="list-style-type: none"> <li>» Frosted</li> <li>» Tempered</li> <li>» Shock- and heat-resistant</li> <li>» Soda-lime glass</li> </ul>
<b>4245</b>	<ul style="list-style-type: none"> <li>» Copper-free aluminum</li> <li>» Stamped and formed</li> <li>» 1/2" knockouts on back and side</li> </ul>	<ul style="list-style-type: none"> <li>» Translucent</li> <li>» Molded</li> <li>» High-impact</li> <li>» Polycarbonate</li> </ul>
<b>4246</b>	<ul style="list-style-type: none"> <li>» Recessed mounting box</li> </ul>	<ul style="list-style-type: none"> <li>» Clear</li> <li>» High-impact</li> <li>» Polycarbonate</li> </ul>
<b>4250</b>	<ul style="list-style-type: none"> <li>» Die-cast</li> <li>» Copper-free aluminum</li> <li>» Surface mounting plate</li> </ul>	<ul style="list-style-type: none"> <li>» Frosted</li> <li>» Tempered</li> <li>» Shock- and heat-resistant</li> <li>» Soda-lime glass</li> </ul>

COVER PLATE
<ul style="list-style-type: none"> <li>» Die-cast</li> <li>» Copper-free aluminum</li> <li>» Superior weather-tight seal</li> </ul>
<ul style="list-style-type: none"> <li>» Fitted with UV-resistant weather stripping</li> </ul>
FINISH
<ul style="list-style-type: none"> <li>» For available options, see ordering information.</li> </ul>
SOCKET/LAMP HOLDER
<ul style="list-style-type: none"> <li>» Proprietary ceramic socket</li> <li>» Nickel contacts</li> </ul>
<ul style="list-style-type: none"> <li>» Stainless steel springs</li> <li>» Teflon-jacketed wire leads</li> </ul>
LAMP TYPE
<ul style="list-style-type: none"> <li>» Standard lamp included. For additional lamp and wattage options see Lamp Guide, pages 128-130.</li> </ul>
PHOTOMETRICS
<ul style="list-style-type: none"> <li>» For photometric data, see pages 131-149.</li> </ul>
FASTENERS/INSERTS
<ul style="list-style-type: none"> <li>» Stainless steel</li> </ul>
WIRING
<ul style="list-style-type: none"> <li>» Prewired with a five-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable.</li> </ul>