





HOUSING/LENS COVER

- » Die-cast copper-free aluminum
- » Silicone O-ring gasket
- » Superior weather-tight seal

FINISH

» Polyester powder-coated finish. See ordering information for available colors.

SOCKET/LAMP HOLDER

- » Proprietary ceramic socket
- » Nickel contacts
- » Stainless steel springs
- » Teflon-jacketed wire leads

OPTICS/AIMING

- » Adjustable and lockable lamp bracket
- $= \pm 25^{\circ}$ of tilt
- » 360° rotation of housing

PHOTOMETRICS

» For photometric data, see pages 131-149.

MOUNTING

- » In-grade
- » Conduit mount option has two ¾" NPT inlets
- » Optional concrete mounting kit available, see page 127.

FASTENERS

» Stainless steel fasteners

» Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable.

	LENS					
5260	» Convex » Clear » Tempered	 » Shock- and heat-resistant » Soda-lime glass » For optical effect lenses, see ordering information. 				
5261	» Convex » Clear » Tempered	 » Shock- and heat-resistant » Soda-lime glass » For optical effect lenses, see ordering information. 				
5262	» Convex » Clear » Tempered	 » Shock- and heat-resistant » Soda-lime glass » For optical effect lenses, see ordering information. 				
5263	 » Dual lens » Frosted flat outer lens » Clear convex inner lens » Tempered 	 » Shock- and heat-resistant » Soda-lime glass » For optical effect lenses, see ordering information. 				

5262 Aluminum 50 W max (halogen) MR-16 Lamp or LED LN-20 BAB/FG Std







LED SPECIFICATIONS 🕏 🔾 Look for this mark on products where LED options are available.

LED Lamp

High Output Plug-in LED lamp with Vista exclusive smart-driver, powered to operate for 30,000 hours with an operating voltage of 9-15 VAC. See page 128 for extended specifications and options.

Integrated LED

High Output LED lamp assembly with Vista exclusive smart-driver, powered to operate for 50,000 hours with an operating voltage of 9-15 VAC. See page 130 for extended specifications and options.

ORDERING INFORMATION Select appropriate choice from each column example: GW-5271-B-BAB/FG-CBL						
Mounting	No.	Finish	Lamp	Lenses/Accessories		
GW In-grade CM In-grade conduit mount	5260 5261 5262 5263 *	B Black Z Architectural Bronze DZ Dark Bronze LZ Light Bronze SB Special Bronze G Verde P Pewter BR Architectural Brick GT Granite TC Terracotta R Rust HG Hunter Green M Mocha WB Weathered Bronze WI Weathered Iron W White	LAMP See reference codes, pages 128-130 INTEGRATED LED See reference codes, page 130, group F	CBL Convex Cool-Blue Lens CFR Convex Frosted Lens SL Flat Spread Lens DBL Flat Dark Blue Lens GL Flat Dark Green Lens RL Flat Red Lens YL Flat Amber Lens HL Honeycomb Louver JBCP-150 Concrete Mounting Kit		

NOTE: not all accessories are available for all fixtures. See footnotes below before ordering.

* No Lenses/Accessories available except for JBCP-150.

Fixtures shipped with standard lamp, unless otherwise specified, and with specified mounting hardware.

