

2216 Aluminum | 50 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB Std



HOUSING/SHROUD	
2216	<ul style="list-style-type: none"> <li>» Die-cast</li> <li>» Copper-free aluminum</li> <li>» Silicone O-ring gasket</li> <li>» Superior weather-tight seal</li> </ul>
2416	<ul style="list-style-type: none"> <li>» Injection-molded, reinforced polymer</li> <li>» Formulated for most Vista polyester powder-coated finishes</li> <li>» Exceptional strength and UV stability</li> <li>» Dual silicone O-ring gaskets</li> <li>» Superior weather-tight seal</li> </ul>
FINISH	
<ul style="list-style-type: none"> <li>» Polyester powder-coated finish. See ordering information for available colors.</li> </ul>	
SOCKET/LAMP HOLDER	
<ul style="list-style-type: none"> <li>» Proprietary ceramic socket</li> <li>» Nickel contacts</li> </ul>	<ul style="list-style-type: none"> <li>» Stainless steel springs</li> <li>» Teflon-jacketed wire leads</li> </ul>
LENS	
<ul style="list-style-type: none"> <li>» Clear</li> <li>» Tempered</li> <li>» Shock- and heat-resistant</li> </ul>	<ul style="list-style-type: none"> <li>» Soda-lime glass</li> <li>» For optical effect lenses, see ordering information.</li> </ul>

LAMP TYPE	<ul style="list-style-type: none"> <li>» Standard lamp included with fixture. For other lamp and wattage options see Lamp Guide, pages 128-130.</li> </ul>
PHOTOMETRICS	<ul style="list-style-type: none"> <li>» For photometric data, see pages 131-149.</li> </ul>
MOUNTING	<ul style="list-style-type: none"> <li>» Adjustable knuckle with 1/2" NPT</li> <li>» Injection-molded, reinforced polymer</li> <li>» Fixture may be mounted into threaded hubs in junction boxes, ground stakes, tree mount boxes, or mounting canopies.</li> <li>» See ordering information for mounting options. For optional mounting accessories, see pages 126-127.</li> </ul>
FASTENERS	<ul style="list-style-type: none"> <li>» Stainless steel fasteners</li> </ul>
WIRING	<ul style="list-style-type: none"> <li>» Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable.</li> </ul>

2416 Composite | 20 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB Std



**LED SPECIFICATIONS**  Look for this mark on products where LED options are available.

**LED Lamp**

High Output Plug-in LED lamp with Vista exclusive smart-driver, powered to operate for 30,000 hours with an operating voltage of 9-15 VAC. See page 128 for extended specifications and options.

**ORDERING INFORMATION** Select appropriate choice from each column

example: **GR-2216-B-BAB-HL**

Mounting	No.	Finish	Lamp	Lenses/Accessories
GR Ground stake	2216	B Black	See reference codes, pages 128-130	BL Flat Cool Blue Lens
WR Wall mount canopy	2416	Z Architectural Bronze*		SL Flat Spread Lens
TR Tree-mount junction box		DZ Dark Bronze		FR Flat Frosted Lens
		LZ Light Bronze		CX Convex Clear Lens
		SB Special Bronze		CFR Convex Frosted Lens
		G Verde		DBL Flat Dark Blue Lens
		P Pewter		GL Flat Dark Green Lens
		BR Architectural Brick		RL Flat Red Lens
		GT Granite		YL Flat Amber Lens
		TC Terracotta		HL Honeycomb Louver
		R Rust		
		HG Hunter Green		
		M Mocha		
		WB Weathered Bronze		
		WI Weathered Iron		
		W White		

NOTE: not all accessories are available for all fixtures. See footnotes below before ordering.

\* Not available for fixtures with composite polymer housings.

Fixtures shipped with standard lamp, unless otherwise specified, and with specified mounting hardware.

