

5006 Aluminum | 5.5 W max | MR-16 LED Lamp | LN 16-4.5-W-36-LED Std



5005 Aluminum | 5.5 W max | MR-16 LED Lamp | LN 16-4.5-W-36-LED Std

**HOUSING/SHROUD**

- › Die-cast
- › Copper-free aluminum
- › Silicone O-ring gasket
- › Superior weather-tight seal

FINISH

- › Polyester powder-coated finish. See ordering information for available colors.

SOCKET/LAMP HOLDER

- › Proprietary ceramic socket
- › Nickel contacts
- › Stainless steel springs
- › Teflon-jacketed wire leads

LENS

- › Clear
- › Tempered
- › Shock- and heat-resistant
- › Soda-lime glass
- › For optical effect lenses, see ordering information.

LAMP TYPE

- › Standard LED lamp included with fixture. For other LED lamp and wattage options see Lamp Guide, page 128.

PHOTOMETRICS

- › For LED lamp photometric data, see pages 131-149.

MOUNTING

- › Adjustable knuckle with 1/2" NPT
- › Injection-molded, reinforced polymer
- › Fixture may be mounted into threaded hubs in junction boxes, ground stakes, tree mount boxes, or mounting canopies.
- › See ordering information for mounting options. For optional mounting accessories, see pages 126-127.

FASTENERS

- › Stainless steel fasteners

WIRING

- › Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable.