



5272 Composite | 50 W max (hal.) | MR-16 Lamp or LED | LN-20 BAB/FG Std



5273 Composite | 35 W max (hal.) | MR-16 Lamp or LED | LN-20 BAB/FG Std



LED SPECIFICATIONS  Look for this mark on products where LED options are available.

LED Lamp	Integrated LED
High Output Plug-in LED lamp with Vista exclusive smart-driver, powered to operate for 30,000 hours with an operating voltage of 9-15 VAC. See page 128 for extended specifications and options.	High Output LED lamp assembly with Vista exclusive smart-driver, powered to operate for 50,000 hours with an operating voltage of 9-15 VAC. See page 130 for extended specifications and options.

ORDERING INFORMATION Select appropriate choice from each column **example: GW-5271-B-BAB/FG-CBL**

Mounting	No.	Finish	Lamp	Lenses/Accessories
GW In-grade	5270	B Black	LAMP See reference codes, pages 128-130	CBL Convex Cool-Blue Lens
CM In-grade conduit mount	5271	DZ Dark Bronze		CFR Convex Frosted Lens
	5272	LZ Light Bronze	INTEGRATED LED See reference codes, page 130, group F	SL Flat Spread Lens
	5273*	SB Special Bronze		DBL Flat Dark Blue Lens
		G Verde		GL Flat Dark Green Lens
		P Pewter		RL Flat Red Lens
		BR Architectural Brick		YL Flat Amber Lens
		GT Granite		HL Honeycomb Louver
		TC Terracotta		JBCP-150 Concrete Mounting Kit
		R Rust		
		HG Hunter Green		
		M Mocha		
		WB Weathered Bronze		
		WI Weathered Iron		
		W White		

NOTE: not all accessories are available for all fixtures. See footnotes below before ordering.
 * No accessory lenses available.
 Fixtures shipped with standard lamp, unless otherwise specified, and with specified mounting hardware.