

5006 Aluminum | 5.5 W max | MR-16 LED Lamp | LN16-4.5-W-36-LED Std



5005 Aluminum | 5.5 W max | MR-16 LED Lamp | LN16-4.5-W-36-LED Std



## HOUSING/SHROUD

- » Die-cast
- » Copper-free aluminum
- » Silicone O-ring gasket
- » Superior weather-tight seal

## FINISH

- » Polyester powder-coated finish. See ordering information for available colors.

## SOCKET/LAMP HOLDER

- » Proprietary ceramic socket
- » Nickel contacts
- » Stainless steel springs
- » Teflon-jacketed wire leads

## LENS

- » Clear
- » Tempered
- » Shock- and heat-resistant
- » Soda-lime glass
- » For optical effect lenses, see ordering information.

## LAMP TYPE

- » Standard LED lamp included with fixture. For other LED lamp and wattage options see Lamp Guide, page 128.

## PHOTOMETRICS

- » For LED lamp photometric data, see pages 131-149.

## MOUNTING

- » Adjustable knuckle with 1/2" NPT
- » Injection-molded, reinforced polymer
- » Fixture may be mounted into threaded hubs in junction boxes, ground stakes, tree mount boxes, or mounting canopies.
- » See ordering information for mounting options. For optional mounting accessories, see pages 126-127.

## FASTENERS

- » Stainless steel fasteners

## WIRING

- » Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable.

5004 Aluminum | 2.5 W max | MR-11 LED Lamp | LN11-2.5-W-36-LED Std



5003 Aluminum | 2.5 W max | MR-11 LED Lamp | LN11-2.5-W-36-LED Std

LED SPECIFICATIONS  Look for this mark on products where LED options are available.

## LED Lamp

High Output Plug-in LED lamp with Vista exclusive smart-driver, powered to operate for 30,000 hours with an operating voltage of 9-15 VAC. See page 128 for extended specifications and options.

## ORDERING INFORMATION Select appropriate choice from each column

example: GR-5005-B-4.5-W-25-SL

Mounting	No.	Finish	Wattage	Color Temp.	Distribution	Lenses/Accessories
GR Ground stake	5003	B Black	2.5	W Warm	15 15° Spot	BL Flat Cool Blue Lens
WR Wall mount canopy	5004	Z Architectural Bronze			25 25° Narrow Flood	SL Flat Spread Lens
TR Tree-mount junction box		DZ Dark Bronze			36 36° Flood	FR Flat Frosted Lens
		LZ Light Bronze			60 60° Wide Flood	DBL Flat Dark Blue Lens
		SB Special Bronze				GL Flat Dark Green Lens
		G Verde				RL Flat Red Lens
		P Pewter				YL Flat Amber Lens
		BR Architectural Brick				HL Honeycomb Louver
		GT Granite				
		TC Terracotta				
		R Rust				
		HG Hunter Green				
		M Mocha				
		WB Weathered Bronze				
		WI Weathered Iron				
		W White				
	5005	(Same as above)	4.5			
	5006		5.5			

NOTE: not all accessories are available for all fixtures. See footnotes below before ordering.  
 Fixtures shipped with standard lamp, unless otherwise specified, and with specified mounting hardware.