




**4260** Aluminum | 10 W max (hal.) | T3.5 Lamp or LED | LN-10 T3.5 Xe Std




**4260M** Aluminum | 10 W max (hal.) | T3.5 Lamp or LED | LN-10 T3.5 Xe Std



**4261** Aluminum | 10 W max (2) (hal.) | T3.5 Lamp (2) or LED | LN-10 T3.5 Xe Std



**4261M** Aluminum | 10 W max (2) (hal.) | T3.5 Lamp (2) or LED | LN-10 T3.5 Xe Std



**HOUSING/MOUNTING**

- » Stainless steel chassis
- » Interlocking flange plate included for masonry installations.

**COVER PLATE**

- Available options:
- » Copper-free aluminum
  - » Solid Brass
  - » Solid Copper
  - » Stainless steel

**FINISH**

- » For available options, see ordering information.

**SOCKET/LAMP HOLDER**

- » Top grade Noryl polymer socket
- » Phosphor bronze contacts
- » PVC-jacketed wire leads
- » Stainless steel lamp holder

**LENS**

- » Frosted
- » Tempered
- » Shock- and heat- resistant
- » Soda-lime glass

**LAMP TYPE**

- » Standard lamp included. For additional lamp and wattage options see Lamp Guide, pages 128-130.

**PHOTOMETRICS**

- » For photometric data, see pages 131-149.

**FASTENERS/INSERTS**

- » Stainless steel

**WIRING**

- » Five-foot pigtail of 18-2 direct-burial cable
- » Underground connectors for secure connection to the supply cable