LESCO® PUSH SPRAYER

	SPECIFICATIONS	
Dimensions	LES-TL80	LES-TL80SS
Weight (empty)	60 lb. (27.2 kg)	60 lb. (27.2 kg)
Overall Length	48" [121.9 cm]	48" (121.9 cm)
Overall Height	31" (78.74 cm) resting position	31" (78.74 cm) resting position
	40" (101.6 cm) working position	40" (101.6 cm) working position
Overall Width	28" [71.12 cm]	28" (71.12 cm)
Operational		
Capacity	12 gallons (45.4 L)	12 gallons (45.4 L)
Spray Zones	Front boom-less nozzle and spot-spraying wand	Front boom-less nozzle and spot-spraying wand
Spraying Width	36" to 48" [91.4 to 121.9 cm]	36" to 48" (91.4 to 121.9 cm)
(Boom-less Nozzle)	Adjustable	Adjustable
Material Capabilities	Any liquid solution	Any liquid solution
	Electrical	
Battery	12v, 7.5 amp hour	12v, 7.5 amp hour
Battery Life	120 gallons (454.2 L) per charge	120 gallons (454.2 L) per charge
Charge Time	12-16 hours	12-16 hours
Pump	0.89 gpm open flow @ 60 PSI	0.89 gpm open flow @ 60 PSI
	Construction	
Frame	Powder-coated steel	Stainless steel
Tank	One piece LLDPE tan poly	One piece LLDPE tan poly
Hose	8' [24 m]	8' [24 m]
Warranty		
	2-year limited	2-year limited

The TL80 lets you forget the hassle of ground driven units. These push sprayers are completely electric-powered. A 12-volt pump provides consistent flow to the adjustable spray wand and the front-mounted, adjustable-height boom-less nozzle, which can spray up to 48 inches wide

Features & Benefits:

- ▲ Electric powered and rechargeable
- ▲ Mobile unit with large pneumatic tires
- ▲ Powder-Coat or Stainless Steel frame
- ▲ Covers approx. 51,000 sq. ft. [1.2 acres]
- ▲ Will spray ANY liquid solution
- ▲ Including ice melt products
- ▲ Adjustable Boom-less nozzle
- ▲ Hand wand for 'spot' spraying
- ▲ Consistent spray pattern
- Ideal for smaller properties, mulch beds, or fenced areas
- ▲ Suitable for spot spraying and lane spraying
- ▲ Will outperform traditional methods and save on labor



