

LESCO® HPS CHARIOT

Easy access to all controls:
Deflector, 3rd Hole Shutoff,
and Hopper On/Off

Speed control lockouts maintain
3.5 MPH during application

Black Powder-Coat
Steel Frame

Injection-molded hopper
with 125 lb capacity

Unique cam operated oscillating
agitator improves particle flow and
will not damage product coating

Over-sized front and rear tires
increase stability and provide
easier applications on taller,
thicker, rougher lawns

Convenient tie-down points for
transporting your HPS

5:1 Gear Ratio & enclosed gear
set provides even product
distribution while protecting
gears from dust & debris



HP Surfer | #102151

Engine	6HP [190CC] Robin Subaru
Transmission	Hydrostatic [rear wheel]
Speed	6 MPH [forward] 3 MPH [reverse]
Frame	Stainless Steel [spreader] Powder Coat Steel [sulky]
Hopper	125 lb. Capacity
Tires	13x6.50-6 [front] ~ Foam filled 18x6.50-8 [rear]
Parking Brake	Foot-operated Disc brake
Dimensions [L x W x H]	60" x 36" x 47"
Weight [Empty]	298 lb.
Warranty [*]	1 Year

*Consult Owners Manual for full warranty details

Optional Accessories

John Deere Landscapes-UL - HPS Chariot Hopper Cover	Minimizes fertilizer dust getting out and moisture getting in
B1705389 - Hour Meter	Easily installs on your HPS Chariot so you know when it is time to perform maintenance
B1009952 - Calibration Gauges	Set and "Fine tune" calibration of your LESCO® spreader
LT650RSC-TRIUMPH - HPS Chariot Carrier	Hitch mounted carrier that fits in any 2" receiver hitch (750# capacity)
007876 - Measuring Wheel	Obtain precise measurement of turf areas; Helps aid in proper calibration of spreaders



800.347.4272 | SiteOne.com