



 **PRO-TRADE<sup>®</sup>**  
LIGHTING



# Built Tough. Priced Right.

Designed to withstand whatever life throws at it, Pro-Trade® gives contractors an enduring solution for professional-grade lighting. Combining a smart value with the convenience and expertise you can only get at SiteOne® Landscape Supply, it's a total package that can't be beat.



## Professional-Grade

Bring on harsh treatment and heavy storms. These ETL-listed lights are built to last.



## No-Nonsense Value

This is about lighting, not bells and whistles. That's why we design these durable products to give you what you need.



## Ready to Go

Drop in and stock up whenever the job demands it. Pro-Trade Lighting is available at your local SiteOne, so you're never stuck waiting for product to arrive.




## FIXTURES

Every model is built with a hefty set of features that ensure they perform season after season without fail. If that's not enough, we back brass models with a lifetime warranty, ledge lights, step lights, and in-ground fixtures with a 10-year warranty, and aluminum models are covered for five years.

### Up Lights

- Heat-Resistant Clear Convex Glass Lens
- High-Temperature Ceramic Socket with Nickel Contacts
- Fixed Socket Assembly
- Dual O-Ring Seals
- EPDM Rubber Plug in Base
- Weather-Resistant SPT-2W Wire
- Includes Ground Stake



FINISH	PRODUCT CODE	HOUSING	LED
 Bronze	PT-BUL1-BZ-NL	Aluminum	Sold Separately
	PT-BUL1-BZ-LED-3FL	Aluminum	MR16 Included: 3W, 38°, 2700K, 250 Lumens
 Black	PT-BUL1-BK-NL	Aluminum	Sold Separately
	PT-BUL1-BK-LED-3FL	Aluminum	MR16 Included: 3W, 38°, 2700K, 250 Lumens
 Antique	PT-BUL1-BS-NL	Brass	Sold Separately
	PT-BUL1-BS-LED-3FL	Brass	MR16 Included: 3W, 38°, 2700K, 250 Lumens



## Flood Lights





- High-Temperature Ceramic Socket with Nickel Contacts
- Silicone Gasket Seal
- EPDM Rubber Plug in Base

- Weather-Resistant SPT-2W Wire
- Includes Ground Stake

PT-FL1-BZ-NL

PT-FL2-BS-LED






FINISH	PRODUCT CODE	HOUSING	LED
 Bronze	PT-FL1-BZ-NL	Aluminum	MR16/T3 Sold Separately
 Black	PT-FL1-BK-NL	Aluminum	MR16/T3 Sold Separately
 Antique	PT-FL1-BS-NL	Brass	MR16/T3 Sold Separately
 Antique	PT-FL2-BS-LED	Brass	T3 Included: 2.5W, 2700K, 180 Lumens

## Path Lights

- Heat-Resistant Polycarbonate Lens
- Dual O-Ring Seals
- EPDM Rubber Plug in Base

- Weather-Resistant SPT-2W Wire
- Includes Ground Stake







FINISH	PRODUCT CODE	HOUSING	DIAMETER	HEIGHT	LED
 Bronze	PT-PTH1-BZ-LED	Aluminum	6.1"	19"	T3 Included: 2.5W, 2700K, 180 Lumens
 Black	PT-PTH1-BK-LED	Aluminum	6.1"	19"	T3 Included: 2.5W, 2700K, 180 Lumens
 Antique	PT-PTH1-BS-LED	Brass	6.1"	19"	T3 Included: 2.5W, 2700K, 180 Lumens

## Ledge Lights

- Stainless Steel Mounting Bracket
- 7" x 0.75" Glare Guard

- Weather-Resistant SPT-1W Wire



FINISH	PRODUCT CODE	HOUSING	LED
 Bronze	PT-LL1-BZ-LED	Aluminum	Included: Four Integrated 1.25W 2700K LEDs
 Black	PT-LL1-BK-LED	Aluminum	Included: Four Integrated 1.25W 2700K LEDs
 Granite	PT-LL1-GT-LED	Aluminum	Included: Four Integrated 1.25W 2700K LEDs
 Gray	PT-LL1-GY-LED	Aluminum	Included: Four Integrated 1.25W 2700K LEDs





### Step Lights

- Surface Mounted (No Cutting Necessary)
- Louvered Brass Face Plate
- Frosted Lens
- Weather-Resistant SPT-1W Wire

PT-SL2-BS-LED PT-SL1-BS-LED




FINISH	PRODUCT CODE	WIDTH	HEIGHT	DEPTH	LED
 Antique	PT-SL1-BS-LED	4.5"	2.9"	0.4"	Integrated 2W 2700K
 Antique	PT-SL2-BS-LED	9"	2.9"	0.4"	Integrated 4W 2700K

### Deck Light

- High-Temperature Ceramic Socket with Nickel Contacts
- Weather-Resistant SPT-2W Wire
- 3.125"W x 1.625"D




FINISH	PRODUCT CODE	HOUSING	LED
 Antique	PT-DL1-BS-LED	Brass	T3 Included: 2.5W, 2700K, 180 Lumens

### Hanging Light

- High Temperature Ceramic Socket with Nickel Contacts
- 5"L x 2.25"W
- 10 Ft. Weather-Resistant SPT-2W Wire
- Optional Lens Included



FINISH	PRODUCT CODE	HOUSING	LED
 Antique	PT-HL1-BS-LED	Brass	T3 Included: 2.5W, 2700K, 180 Lumens


In-Ground Lights

- High-Temperature Ceramic Socket with Nickel Contacts
  - Injection-Molded Polyester Fiberglass Composite Housing
- Rubber Gasket Seal
  - 4.9" Diameter Cast Brass Cover
  - Weather-Resistant VW-1 Wire

PT-IG1-BS-NL

PT-IG2-BS-NL




FINISH	PRODUCT CODE	HOUSING	COVER	LED
 Antique	PT-IG1-BS-NL	Composite	Clear Brass Cover	MR16 Sold Separately
	PT-IG2-BS-NL	Composite	Louvered Brass Cover	MR16 Sold Separately

Well Light

- 8" Height x 5.5" Diameter Black ABS Well Sleeve
- Adjustable Stainless Steel PAR36 Gimbal
  - Weather-Resistant SPT-1W Wire Includes Two Spade Connectors



FINISH	PRODUCT CODE	HOUSING	LED
 Black	PT-WL1-BK-NL	ABS	PAR36 Sold Separately





# LED LAMPS

It's time to put an end to dark corners and dim landscapes. These powerful LED lamps are rated for enclosed fixtures and damp locations, and they're all backed by a five-year or a lifetime warranty.

## MR16 LED Lamps


- 3W - 7W
- 2700K or 3000K
- 250-550 Lumens
- 38° or 60° Beam Spread



PRODUCT CODE	INPUT VOLTAGE	WATTAGE	VA	COLOR TEMP	BEAM SPREAD	LUMENS	AVERAGE RATED LIFE	WARRANTY
PT-MR16-3FL-27	10-18V	3W	4.3VA	2700K	38°	250	30,000 Hrs	5 Years
PT-MR16-3WF-27	10-18V	3W	4.3VA	2700K	60°	250	30,000 Hrs	5 Years
PT-MR16XL-4FL-27	8-18V	4W	5.7VA	2700K	38°	325	50,000 Hrs	Lifetime
PT-MR16XL-4WF-27	8-18V	4W	5.7VA	2700K	60°	325	50,000 Hrs	Lifetime
PT-MR16-5FL-27	10-18V	5W	7.1VA	2700K	38°	350	30,000 Hrs	5 Years
PT-MR16-5WF-27	10-18V	5W	7.1VA	2700K	60°	350	30,000 Hrs	5 Years
PT-MR16XL-5.5FL-27	8-18V	5.5W	7.9VA	2700K	38°	380	50,000 Hrs	Lifetime
PT-MR16XL-5.5WF-27	8-18V	5.5W	7.9VA	2700K	60°	380	50,000 Hrs	Lifetime
PT-MR16XL-5.5FL-30	8-18V	5.5W	7.9VA	3000K	38°	400	50,000 Hrs	Lifetime
PT-MR16XL-5.5WF-30	8-18V	5.5W	7.9VA	3000K	60°	400	50,000 Hrs	Lifetime
PT-MR16-7FL-27	10-18V	7W	10VA	2700K	38°	550	30,000 Hrs	5 Years
PT-MR16-7WF-27	10-18V	7W	10VA	2700K	60°	550	30,000 Hrs	5 Years

## T3 LED Lamps

- Ceramic or Water-Resistant Silicone
- 1.2W-3.5W
- 2700K or 3000K
- G4 or SCB Base
- 100-230 Lumens



PRODUCT CODE	BASE	INPUT VOLTAGE	WATTAGE	VA	COLOR TEMP	LUMENS	AVERAGE RATED LIFE	MOL	WARRANTY
PT-T3XL-1.2-27-CM	G4	10-14V	1.2W	1.7VA	2700K	100	35,000 Hrs	1.33"	Lifetime
PT-T3XL-2-27-CM	G4	8-25V	2W	2.8VA	2700K	200	35,000 Hrs	1.80"	Lifetime
PT-T3XL-2-27-CM-SCB	SCB	8-25V	2W	2.8VA	2700K	200	35,000 Hrs	2.04"	Lifetime
PT-T3-2.5-27	G4	10-15V	2.5W	3.6VA	2700K	180	25,000 Hrs	1.37"	5 Years
PT-T3-3.5-27	G4	10-15V	3.5W	5VA	2700K	230	25,000 Hrs	1.6"	5 Years
PT-T3-3.5-30	G4	10-15V	3.5W	5VA	3000K	230	25,000 Hrs	1.6"	5 Years



### T5 LED Lamps

- Water-Resistant Ceramic
- 1.2W or 2W
- 2700K
- Wedge Base
- 120 or 200 Lumens



PRODUCT CODE	BASE	INPUT VOLTAGE	WATTAGE	VA	COLOR TEMP	LUMENS	AVERAGE RATED LIFE	MOL	WARRANTY
PT-T5XL-1.2-27-CM	Wedge	10-14V	1.2W	1.7VA	2700K	120	35,000 Hrs	1.33"	Lifetime
PT-T5XL-2-27-CM	Wedge	8-25V	2W	2.8VA	2700K	200	35,000 Hrs	1.75"	Lifetime

### S8 LED Lamp

- Water-Resistant Ceramic
- 2W
- 2700K
- Wedge Base
- 200 Lumens



PRODUCT CODE	BASE	INPUT VOLTAGE	WATTAGE	VA	COLOR TEMP	LUMENS	AVERAGE RATED LIFE	MOL	WARRANTY
PT-S8XL-2-27-CM	Wedge	8-25V	2W	2.8VA	2700K	200	35,000 Hrs	2.17"	Lifetime

### PAR36 LED Lamps

- Chip on Board (COB) Technology
- 400-800 Lumens
- IP67 Rated
- 6W-11W
- 40° Beam Spread



PRODUCT CODE	INPUT VOLTAGE	WATTAGE	VA	COLOR TEMP	BEAM SPREAD	LUMENS	AVERAGE RATED LIFE	MOD	WARRANTY
PT-PAR36-6FL-27	10-15V	6W	8.6VA	2700K	40°	400	30,000 Hrs	4.37"	5 Years
PT-PAR36-8FL-27	10-15V	8W	11.4VA	2700K	40°	600	30,000 Hrs	4.37"	5 Years
PT-PAR36-11FL-27	10-15V	11W	15.7VA	2700K	40°	800	30,000 Hrs	4.37"	5 Years



## TRANSFORMERS

Your lighting is only as reliable as the power behind it. That's why we design dependable transformers that keep your landscapes lit and your customers satisfied. Even better, they're all backed by a lifetime warranty.

### Stainless Steel Transformers

- Stainless Steel Case
- Removable, Lockable Door
- Overload Protection with Auto Thermal Shut-Off
- Secondary Side Magnetic Circuit Breakers
- Pre-Punched Bottom Panel for 1.25" Conduit
- Plug-In Photocell Ready
- Quick-Mount Bracket

PRODUCT CODE	POWER RATING	PRIMARY VOLTAGE	SECONDARY VOLTAGE
PT-TR1-150SS	150W	120V	12V, 13V, 14V, & 15V
PT-TR1-300SS	300W	120V	12V, 13V, 14V, & 15V



## ACCESSORIES

Give your customers the convenience of lighting on their schedule. Timers and photocells allow for preset hours of illumination or auto-on during low daylight hours.

PRODUCT CODE	DESCRIPTION
PT-MT1	Mechanical Timer
PT-PC1	Photocell



## LET'S TALK

When you buy lighting at SiteOne, expertise is always included in the package. So call your branch and ask about putting these products to work for your business.