




Arrow-Breaker® hose bibs

261LF - 361LF




262LF



263LF - 363LF



264CCLF



features

- heavy duty lead-free bronze.
- patented Arrow-Breaker®: built-in anti-siphon back-flow preventer that protects your water supply from harmful contaminants.
- ASSE 1011 approved, IAPMO certified.
- exclusive one piece O-ring style bonnet & green tee handle.
- 3-year limited warranty.
- max pressure: 125 PSI.
- max temperature: 180° F.
- high flow rate: 11-12 gallons per minute at 50 PSI.

base model	261LF	361LF	262LF
description	no-kink hose bib 1/2 MIP lead free	no-kink hose bib 3/4 MIP lead free	no-kink hose bib 1/2 or 3/4 SWT lead free
weight (lbs)	0.59	0.602	0.59
pack qty	12	12	12
case qty	72	72	72



base model	263	363LF	264CCLF
description	no-kink hose bib 1/2 FIP lead free	no-kink hose bib 3/4 FIP lead free	no-kink hose bib 1/2 compression lead free
weight (lbs)	0.518	0.552	0.59
pack qty	12	12	12
case qty	72	72	72

available options

loose key & less key



261LKLF
LK: lock-shield with key
LS: lock-shield; no key

repair & replacement parts

replacement stem assembly



PK1600
replacement Arrow-Breaker® stem & bonnet assembly (1-9)

loose key stem assembly



PK1600LK
Arrow-Breaker® loose key & lock-shield stem assembly

replacement tee handle & screw



PK1270
green tee handle (10) & handle screw (11)

1/2" copper compression kit



PK1180
replacement compression nut and ferrule for 221CCRBLF

