

# PGP® ULTRA & I-20 PRB

Radius: **17' to 46'**  
Flow: **0.36 to 9.8 GPM**

The PGP Ultra and I-20 PRB are built to thrive in applications where high water pressure could otherwise lead to inefficient nozzle operation.

## KEY BENEFITS

- Pressure-regulated body (45 PSI) reduces high incoming pressure to increase nozzle efficiency
- Patented automatic arc return feature returns the turret back to the original arc pattern if vandalized; adjustable arc from 50° to 360°
- Non-strippable drive mechanism is protected from damage if turned in the opposite direction of travel
- Part- and full-circle in one model for flexibility across landscapes and reduced inventory
- Headed and slotted setscrew allows radius adjustment with a Hunter wrench or flat-blade screwdriver
- FloStop® closes the flow of water from individual sprinklers, to change the nozzle or perform repairs (I-20 only)
- Flat-top nozzles allow fast, easy insertion
- QuickCheck™ arc mechanism for fast arc adjustment
- Available stainless steel riser for extra durability
- Drain check valve prevents low-head drainage (up to 10' of elevation)

## OPERATING SPECIFICATIONS

- Nozzle choices: 30
- Radius: 17' to 46'
- Flow: 0.36 to 9.8 GPM
- Nozzle discharge pressure: 45 PSI
- Operating pressure range: 20 to 100 PSI
- Precipitation rate: 0.4 in/hr approximately
- Nozzle trajectory: standard = 25°, low-angle = 13°
- Nozzle racks: 1.5 to 8.0 blue, 2.0 to 4.5 low-angle gray, 0.50 to 3.0 black, MPR-25, MPR-30, MPR-35
- Warranty period: 5 years

## FACTORY-INSTALLED OPTIONS

- Reclaimed water ID
- Blue #1.5-4.0 nozzles

## USER-INSTALLED OPTIONS

- HSJ-0 prefabricated ¾" PVC swing joint



### PGP-00-PRB

Overall height: 8⅝"  
Exposed diameter: 1¼"  
Inlet size: ¾"

### PGP-04-PRB

Overall height: 8¼"  
Pop-up height: 4"  
Exposed diameter: 1¾"  
Inlet size: ¾"



### I-20-00-PRB

Overall height: 8⅝"  
Exposed diameter: 1¼"  
Inlet size: ¾"

### I-20-04-PRB

Overall height: 8¼"  
Pop-up height: 4"  
Exposed diameter: 1¾"  
Inlet size: ¾"



### I-20-06-PRB

Overall height: 10⅝"  
Pop-up height: 6"  
Exposed diameter: 1¾"  
Inlet size: ¾"

## PGP-ULTRA & I-20 PRB – SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
<b>PGP-00-PRB</b> = Riser mount  <b>PGP-04-PRB</b> = 4" pop-up	Adjustable arc, plastic riser, pressure-regulated body, 8 standard nozzles, and 4 low-angle nozzles	<b>(blank)</b> = No option  <b>CV</b> = Drain check valve (PGP-04 only)  <b>CV-R</b> = Drain check valve and reclaimed water ID	<b>Blue 1.5-8.0</b> = Factory-installed nozzle number <b>Gray low-angle</b> <b>Black short-radius</b> <b>MPR-25, 30, 35 - Q, T, H, F</b>
<b>I-20-00-PRB</b> = Shrub  <b>I-20-04-PRB</b> = 4" pop-up  <b>I-20-06-PRB</b> = 6" pop-up	Adjustable arc, plastic riser, pressure-regulated body, 8 standard nozzles, and 4 low-angle nozzles	<b>(blank)</b> = No option  <b>R</b> = Drain check valve and reclaimed water ID	<b>Blue 1.5-8.0</b> = Factory-installed nozzle number <b>Gray low-angle</b> <b>Black short-radius</b> <b>MPR-25, 30, 35 - Q, T, H, F</b>
<b>I-20-04-SS-PRB</b> = 4" pop-up  <b>I-20-06-SS-PRB</b> = 6" pop-up	Adjustable arc, stainless steel riser, pressure-regulated body, 8 standard nozzles, and 4 low-angle nozzles	<b>(blank)</b> = No option  <b>R</b> = Drain check valve and reclaimed water ID	<b>Blue 1.5-8.0</b> = Factory-installed nozzle number <b>Gray low-angle</b> <b>Black short-radius</b> <b>MPR-25, 30, 35 - Q, T, H, F</b>

### Examples:

- PGP-04-PRB = 4" pop-up, adjustable arc, plastic riser with no factory installed-nozzle
- I-20-04-PRB-3.0-2.5 = 4" pop-up, adjustable arc, plastic riser with 3.0 nozzle
- I-20-06-SS-PRB-R-MPR-25H = 6" pop-up, adjustable arc, stainless steel riser with MPR-25H