

Permatex, Inc.  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924  
 International Emergency: +01-813-248-0585

5106-3

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** 51D PIPE JOINT COMPOUND 1PT  
**Item No:** 80045  
**Product Type:** Sealant

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
KAOLIN 1332-58-7	30-40	2 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>
VEGETABLE OIL 68187-84-8	15-25	5 mg/m <sup>3</sup>	Not listed
ROSIN 8050-09-7	15-25	Not listed	Not listed
ETHANOL 64-17-5	5-15	1000 ppm	1000 ppm; 1900 mg/m <sup>3</sup>
TALC 14807-96-6	<10	2 mg/m <sup>3</sup>	20 mppcf
2-PROPANOL 67-63-0	<2	200 ppm	400 ppm; 980 mg/m <sup>3</sup>
METHANOL 67-56-1	0.1-1.0	200 ppm	200 ppm; 260 mg/m <sup>3</sup>
TITANIUM DIOXIDE 13463-67-7	0.1-1.0	10 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>
SILICA, QUARTZ 14808-60-7	0.1-1.0	0.025 mg/m <sup>3</sup>	Not listed

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause eye, skin and respiratory irritation. This product contains encapsulated silicon dioxide (quartz silica). No exposure to free respirable silica is anticipated during normal use of this product. Silica may be released by grinding or machining of coated material. Use NIOSH-approved dust/mist respirator when grinding or machining.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation

**Signs and Symptoms of Exposure:** Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. Overexposure may cause eye and skin redness.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
KAOLIN 1332-58-7	30-40		A4-Not classifiable as a human carcinogen	

**Product Name:** 51D PIPE JOINT COMPOUND 1PT**Item No:** 80045

Component	Weight%	NTP	ACGIH Carcinogens	IARC
ETHANOL 64-17-5	5-15		A4 - Not Classifiable as a Human Carcinogen	
TALC 14807-96-6	<10	male rat-some evidence, female rat-clear evidence, male mice-no evidence, female mice-no evidence	A4- Not classifiable as a human carcinogen	Group 3 Supplement 7, 1987 Monograph 42, 1987
2-PROPANOL 67-63-0	<2		A4 - Not classifiable as a human carcinogen	Group 3 Monograph 71, 1999; Supp.7, 1987; Monograph 15, 1977
TITANIUM DIOXIDE 13463-67-7	0.1-1.0	male rat-negative, female rat-negative, male mice-negative, female mice-negative	A4	Group 2B; Vol 93,2006; Vol 47,1989
SILICA, QUARTZ 14808-60-7	0.1-1.0		A2 - Suspected Human Carcinogen	Group 1; Monograph 68, 1997

**Medical Conditions Recognized as Being Aggravated by Exposure:** Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

#### 4. FIRST AID MEASURES

**Ingestion:** Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.

**Skin Contact:** Wash off with soap and water. If skin irritation persists, call a physician.

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

#### 5. FIRE FIGHTING MEASURES

**Flash Point °F(C°):** 76°F TCC

**Recommended Extinguishing Media:** Carbon Dioxide, Dry Chemicals, Foam.

**Special Fire-Fighting Procedures:** Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

**Hazardous Products of Combustion:** Aldehydes, Oxides of carbon, Carboxylic acids

**Unusual Fire/Explosion Hazards:** Closed containers may rupture or explode when exposed to extreme heat.

**Lower Explosive Limit:** 2.3

**Upper Explosive Limit:** 12.7

#### 6. ACCIDENTAL RELEASE MEASURES

**Spill Procedures:** Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Residues may be cleaned up with isopropyl alcohol.

#### 7. HANDLING AND STORAGE

**Storage:** Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C).

**Handling:** Avoid contact with skin and eyes. Do not inhale vapors. Keep container closed when not in use.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Eyes:** Safety glasses.

**Skin:** Rubber or plastic gloves.

**Ventilation:** General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

**Respiratory Protection:** An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Black paste

**Odor:** Alcohol

**Boiling Point:** 180 degrees F.

**pH:** Does not apply

**Product Name:** 51D PIPE JOINT COMPOUND 1PT

**Item No:** 80045

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Solubility in Water:</b>	Partial
<b>Specific Gravity:</b>	1.25-1.32
<b>VOC(Wt.%):</b>	14.2%; 182.9 g/l
<b>Vapor Pressure:</b>	33 mm Hg @ 68 degrees F.
<b>Vapor Density (Air=1):</b>	>1
<b>Evaporation Rate:</b>	Not available

## 10. STABILITY AND REACTIVITY

<b>Chemical Stability:</b>	Stable at normal conditions
<b>Hazardous Polymerization:</b>	Will not occur.
<b>Incompatibilities:</b>	Strong oxidizers
<b>Conditions to Avoid:</b>	Keep away from heat, sparks and open flame. - No smoking.
<b>Hazardous Products of Combustion:</b>	Aldehydes, Oxides of carbon, Carboxylic acids

## 11. TOXICOLOGICAL INFORMATION

See Section 3

## 12. ECOLOGICAL INFORMATION

No data available

## 13. DISPOSAL CONSIDERATIONS

<b>Recommended Method of Disposal:</b>	Disposal should be made in accordance with federal, state and local regulations..
<b>US EPA Waste Number:</b>	D001 as per 40CFR 261.21

## 14. TRANSPORTATION INFORMATION

### DOT (49CFR 172)

#### Ground Transport (DOT)

<b>DOT Shipping Name:</b>	Consumer Commodity (not more than one liter)
<b>Hazard Class:</b>	ORM-D
<b>UN/ID Number:</b>	None

#### IATA

<b>Proper Shipping Name:</b>	Consumer Commodity (Not more than 1 liter)
<b>Class or Division:</b>	Class 9
<b>UN/ID Number:</b>	ID 8000

#### IMDG

<b>Proper Shipping:</b>	Resin Solution, Flammable, Limited Quantity
<b>Hazard Class:</b>	Class 3 PGIII
<b>UN Number:</b>	UN 1866

**Marine Pollutant:** None

## 15. REGULATORY INFORMATION

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

**California Proposition 65:** No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level

**TSCA Inventory Status:** All components of this product are listed (or exempt) on the EPA TSCA inventory.

## 16. OTHER INFORMATION

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 3, REACTIVITY 0.

**Estimated HMIS Classification:** HEALTH 2, FLAMMABILITY 3, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Product Name:** 51D PIPE JOINT COMPOUND 1PT

**Item No:** 80045

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

**Revision Date:** January 07, 2008  
**Revision Number:** 3

**Telephone No.:** 1-87-Permatex (877) 376-2839