

Molded Plastic Well Points

One piece molded construction
 Sizes 1-1/4" to 4" may be glued inside
 SCH. 40 plastic pipe.

Part No.	Pipe Size	Case Qty
BWP-125-40	1-1/4" SCH. 40	50
BWP-150-40	1-1/2" SCH. 40	50
BWP-200-40	2" SCH. 40	25
BWP-300-40	3" SCH. 40	20
BWP-400-40	4" SCH. 40	15

Pump Perfect

The Brady Pump Perfect is available in four standard sizes, for water well applications, or lake, pond, canal and river applications. The Brady Pump Perfect can be custom fabricated for any specific application. The standard discharge cone is 1-1/4". Other discharge sizes are available upon request.

Model No.	Overall Length	Ft. Slotted	OD	ID	Discharge Pipe Size
BPP 405-010	63"	3"	4.50"	3.996"	1.25"
BPP 410-010	123"	7"	4.50"	3.998"	1.25"
BPP 405-040	63"	3"	4.50"	3.998"	1.25"
BPP 410-040	123"	7"	4.50"	3.998"	1.25"

Jet Points

Jet Points are used primarily for shallow dewatering applications.
 Molded plastic construction
 Sizes 1-1/4", 1-1/2" & 2" SCH. 40
 Poly Ball Check
 Internal FIP Threads
 Glues to Well Screen for wash down

Part No.	Wgt.(lbs.)	Case Qty
BJP-125-40	1-1/4"	50
BJP-150-40	1-1/2"	50
BJP-200-40	2"	25

Slip Caps & Plugs

Designed to be solvent glued.
 One piece molded plastic construction
 Plugs Fit ID SCH. 40 Plastic Pipe

Slip Caps Available in Sizes -

1" to 8"

Slip Plugs Available in Sizes -

1" to 12"

Flush Thread Screens

Constructed of high quality SCH 40 PVC Pipe
 Precision slotted for maximum flow
 Available in sizes 2" to 12"
 Standard length 2-1/2', 5', 10', & 20'
 Individually wrapped "when required" in poly bags
 Buna-N Rubber "O" Ring
 Threads meet F 480 specifications
 Standard slot sizes .010 & .020
 Custom slotting available upon request

Flush Threaded Casing

Constructed of high quality SCH 40 PVC Pipe
 Available in sizes 2" to 12"
 Standard length 2-1/2', 5', 10' & 20'
 Individually wrapped "when required" in poly bags
 Buna-N Rubber "O" Ring
 Threads meet F 480 Specifications
 custom lengths available upon request

Sales: 800-523-0224