



DOLOMITIC LIMESTONE MICRO-SELECT PRILL

- *Corrects Soil pH*
- *Improved Nutrient Availability*
- *Adds Essential Magnesium & Calcium*
- *Activates Microorganisms*
- *100% Natural*
- *Will Not Burn*

 **SOUTHDOWN, INC.**

**FOR PROFESSIONAL USE ONLY
NET WT. 50 LBS. (22.7 Kg)**

DOLOMITIC LIMESTONE



DOLOMITIC LIMESTONE PRO-SELECT PRILL

GUARANTEED MINIMUM CHEMICAL ANALYSIS

ELEMENTAL CALCIUM (Ca)	21%
CALCIUM OXIDE (CaO)	29%
CALCIUM CARBONATE (CaCO ₃)	52%
ELEMENTAL MAGNESIUM (Mg)	10%
MAGNESIUM OXIDE (MgO)	17%
MAGNESIUM CARBONATE (MgCO ₃)	35%
CALCIUM CARBONATE EQUIVALENT (CCE)	50%
TOTAL OXIDES	48%
TOTAL CARBONATES	87%
EFFECTIVE NEUTRALIZING VALUE (ENV)	84%

F-1266

GUARANTEED MINIMUM PHYSICAL ANALYSIS (Before Pelletizing)

SCREEN SIZE	% PASSING
8 MESH	100%
16 MESH	100%
30 MESH	100%
40 MESH	100%
60 MESH	100%
80 MESH	100%
100 MESH	100%
200 MESH	60%
MOISTURE MAXIMUM	1%

CAS NUMBER - 16289-88-1

FLORIDA

This product requires 1638 pounds to equal 1 ton of standard liming material using calculated CCE. The guaranteed analysis is a minimum amount. Calcium carbonate, magnesium and CCE percentages may exceed these amounts.

NORTH CAROLINA

1640 pounds of this material equals 1 ton of standard liming material.

OHIO

Total Heating Power (THP) = 85.7 BHP -4775 Btu/ton

PENNSYLVANIA

Agricultural Liming Material Classification - Fine Stone

TENNESSEE

Relative Neutralizing Value (RNW) = 81.9%

SUGGESTED SPREADER SETTINGS (Pounds per 1000 Square Feet)

	100'	500'	600'
CENTRAL 80	6-1/2	8	10
CYCLONE	5	7	8'
EVAN-SPREAD	16-1/2	20	24
FRANKS	3	7-1/2	10-1/2
LESCO	2	4	5
SCOTT'S 80 1	9	6-1/2	10
SCOTT'S PROPERT (EPCO)	6-1/2	8	10
SEARS	8-1/2	4-1/2	8-1/2
SEARS (EPCO)	5-1/2	7	10
SPYDER	4-1/2	8-1/2	6-1/2

*Requires 2 passes for recommended coverage. Actual settings depend on type, model & condition of spreader.

FOR INCORPORATION - AFTER APPLICATION - WET THOROUGHLY 30 MINUTES BEFORE TILLING

PRODUCT SAFETY INFORMATION WARNING

This product may contain greater than 0.5% silica which has been linked to chronic respiratory disease. Prolonged inhalation of respirable crystalline silica may have carcinogenic effects.

USE APPROVED RESPIRATOR IN DUSTY AREAS.
AVOID BREATHING IRRIANT DUST. USE WITH ADEQUATE VENTILATION.
FIRST AID: IF SWALLOWED WITH WATER OR MILK. MOVE TO FRESH AIR.
SEE MATERIAL SAFETY DATA SHEET (MSDS) FOR ADDITIONAL INFORMATION.

SOUTHDOWN, INC.

Product Guaranteed by:
Southdown, Inc.

2200 Sullivan Trail
Gordon, Pennsylvania 16040
1-800-826-1753

Plants Located In: Charlottesville, VA & Parsippany, PA



PRO-SELECT PRILL

by SOUTHDOWN