

# I-25

Radius: **37' to 71'**  
 Flow: **3.8 to 31.5 GPM**  
 Inlet: **1"**

## FEATURES

- Models plastic riser: 4", 6"
  - Models stainless steel riser: 4", 6"
  - Arc setting: 50° to 360°
  - Factory installed rubber cover
  - Through-the-top arc adjustment
  - QuickCheck™ arc mechanism
  - Water lubricated gear-drive
  - Nozzle choices: 12
  - Nozzle range: #4 to #28
  - Warranty period: 5 years
- ▶ Automatic arc return
  - ▶ Non-strippable drive
  - ▶ Part- and full-circle in one model
  - ▶ Color-coded nozzles
  - ▶ Reclaimed water ID
  - ▶ Stainless steel riser
  - ▶ Drain check valve (up to 10' of elevation)

## OPERATING SPECIFICATIONS

- Radius: 37' to 71'
- Flow: 3.8 to 31.5 GPM
- Recommended pressure range: 40 to 100 PSI
- Operating pressure range: 40 to 100 PSI
- Precipitation rates: 0.4 in/hr approximately
- Nozzle trajectory: 25°

▶ = *Advanced Feature descriptions on page 30*



**I-25-04**  
 Overall height: 7⅞"  
 Pop-up height: 4"  
 Exposed diameter: 1¾"  
 Inlet size: 1"



**I-25-06**  
 Overall height: 10¼"  
 Pop-up height: 6"  
 Exposed diameter: 1¾"  
 Inlet size: 1"



**I-25 Reclaimed**  
 Available as a factory installed option on all models



**I-25 High Speed**  
 Available as a factory installed option on stainless steel models

### I-25 (PLASTIC) - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-25-04 = 4" Pop-up I-25-06 = 6" Pop-up	Adjustable arc, plastic riser, check valve, and 5 nozzles	(blank) = No option R = Reclaimed water ID	#4 to #28 = Factory installed nozzle number

### I-25 (STAINLESS STEEL) - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-25-04-SS = 4" Pop-up I-25-06-SS = 6" Pop-up	Adjustable arc, stainless steel riser, check valve, and 5 nozzles	(blank) = No option R = Reclaimed water ID HS = High speed HS-R = High speed and reclaimed water ID	#4 to #28 = Factory installed nozzle number

**Examples:**


- I-25-04 = 4" Pop-up, adjustable arc
- I-25-04-SS - R - 18 = 4" Pop-up, adjustable arc, stainless steel riser, reclaimed water ID, and #18 nozzle
- I-25-06-SS = 6" Pop-up, adjustable arc, stainless steel riser

ROTORS

ROTORS

I-25 STANDARD NOZZLE PERFORMANCE DATA					
Nozzle	Pressure PSI	Radius ft.	Flow GPM	Precip in/hr	
				■	▲
<b>04</b> ● Yellow	40	40	3.8	0.46	0.53
	50	41	4.3	0.49	0.57
	60	42	4.7	0.51	0.59
	70	43	5.1	0.53	0.61
<b>05</b> ○ White	40	43	4.4	0.46	0.53
	50	44	4.8	0.48	0.55
	60	45	5.3	0.50	0.58
	70	46	5.6	0.51	0.59
<b>07</b> ● Orange*	40	45	6.6	0.63	0.72
	50	47	7.0	0.61	0.70
	60	48	7.5	0.63	0.72
	70	49	7.9	0.63	0.73
<b>08</b> ● Lt. Brown	40	47	7.7	0.67	0.77
	50	49	8.3	0.67	0.77
	60	50	9.2	0.71	0.82
	70	51	9.9	0.73	0.85
<b>10</b> ● Lt. Green*	50	51	10.1	0.75	0.86
	60	52	11.1	0.79	0.91
	70	53	12.1	0.83	0.96
	80	54	12.9	0.85	0.98
<b>13</b> ● Lt. Blue	50	53	11.2	0.77	0.89
	60	54	12.3	0.81	0.94
	70	55	13.3	0.85	0.98
	80	55	14.3	0.91	1.05
<b>15</b> ● Gray*	50	56	13.4	0.82	0.95
	60	57	14.3	0.85	0.98
	70	57	15.2	0.90	1.04
	80	58	16.4	0.94	1.08
<b>18</b> ● Red	50	58	14.5	0.83	0.96
	60	59	15.7	0.87	1.00
	70	62	16.9	0.85	0.98
	80	63	18.2	0.88	1.02
<b>20</b> ● Dk. Brown*	60	62	17.8	0.89	1.03
	70	63	19.2	0.93	1.08
	80	64	20.5	0.96	1.11
	90	65	21.8	0.99	1.15
<b>23</b> ● Dk. Green	60	64	21.9	1.03	1.19
	70	65	23.6	1.08	1.24
	80	66	25.6	1.13	1.31
	90	67	27.0	1.16	1.34
<b>25</b> ● Dk. Blue*	60	66	23.5	1.04	1.20
	70	68	25.5	1.06	1.23
	80	69	28.0	1.13	1.31
	90	70	29.5	1.16	1.34
<b>28</b> ● Black	70	68	26.9	1.12	1.29
	80	70	28.7	1.13	1.30
	90	71	30.6	1.17	1.35
	100	71	31.5	1.20	1.39

I-25 HIGH-SPEED NOZZLE PERFORMANCE DATA					
Nozzle	Pressure PSI	Radius ft.	Flow GPM	Precip in/hr	
				■	▲
<b>04</b> ● Yellow	40	37	3.8	0.53	0.62
	50	38	4.3	0.57	0.66
	60	38	4.7	0.63	0.72
	70	39	5.1	0.65	0.75
<b>05</b> ○ White	40	38	4.4	0.59	0.68
	50	39	4.8	0.61	0.70
	60	40	5.3	0.64	0.74
	70	41	5.6	0.64	0.74
<b>07</b> ● Orange*	40	40	6.6	0.79	0.92
	50	41	7.0	0.80	0.93
	60	42	7.5	0.82	0.95
	70	44	7.9	0.79	0.91
<b>08</b> ● Lt. Brown	40	42	7.7	0.84	0.97
	50	43	8.3	0.86	1.00
	60	44	9.2	0.91	1.06
	70	45	9.9	0.94	1.09
<b>10</b> ● Lt. Green*	50	46	10.1	0.92	1.06
	60	48	11.1	0.93	1.07
	70	49	12.1	0.97	1.12
	80	50	12.9	0.99	1.15
<b>13</b> ● Lt. Blue	50	48	11.2	0.94	1.08
	60	49	12.3	0.99	1.14
	70	51	13.3	0.98	1.14
	80	51	14.3	1.06	1.22
<b>15</b> ● Gray*	50	49	13.4	1.07	1.24
	60	51	14.3	1.06	1.22
	70	53	15.2	1.04	1.20
	80	54	16.4	1.08	1.25
<b>18</b> ● Red	50	50	14.5	1.12	1.29
	60	53	15.7	1.08	1.24
	70	55	16.9	1.08	1.24
	80	57	18.2	1.08	1.25
<b>20</b> ● Dk. Brown*	60	53	17.8	1.22	1.41
	70	56	19.2	1.18	1.36
	80	58	20.5	1.17	1.35
	90	59	21.8	1.21	1.39
<b>23</b> ● Dk. Green	60	56	21.9	1.34	1.55
	70	58	23.6	1.35	1.56
	80	60	25.6	1.37	1.58
	90	61	27.0	1.40	1.61
<b>25</b> ● Dk. Blue*	60	58	23.5	1.34	1.55
	70	62	25.5	1.28	1.47
	80	64	28.0	1.32	1.52
	90	66	29.5	1.30	1.51
<b>28</b> ● Black	70	60	26.9	1.44	1.66
	80	62	28.7	1.44	1.66
	90	65	30.6	1.39	1.61
	100	67	31.5	1.35	1.56



\* 5 standard nozzles included with each sprinkler.

**Note:**  
All precipitation rates calculated for 180° operation. For the precipitation rate for a 360° sprinkler, divide by 2.