

HydroCover™ – #088900 EzFlo™ Blend Hydraulic Mulch

High quality mulch for jet-agitated machines



Advantages:

- Provides optimum pumping and application performance for both jet-agitated and mechanically-agitated equipment
- Loose packing makes loading and mixing faster and easier
- Combines hammermilled wood fiber with the highest quality cellulose mulch in the industry
- Delivers greater yield to contractors versus competitive cellulose products
- Covers up to 20% more ground than 100% cellulose and provides superior erosion control and more complete germination without a jump in price
- Enhances water-holding capacity, reducing soil erosion while improving turf coverage
- Provides superior erosion control and germination performance compared to 100% cellulose fiber
- Non-toxic, environmentally safe and biodegradable
- Maximum slope length of 23 feet at $\leq 4H:1V$ slope
- HydroCover™ EzFlo™ Blend functional longevity is ≤ 3 months

Product Composition:

Wood Fiber – 41.5% \pm 15%
 Cellulose Fiber – 41.5% \pm 15%
 Wood Fiber (maximum) – 56.5%
 Cellulose Fiber (minimum) – 26.5%
 Linear Tackifier – 5% \pm 1%
 Moisture Content – 12% \pm 3%
 (40) 40-lb bales per pallet

Slope Gradient/Condition

$\leq 4H:1V$

$> 4H:1V$ and $\leq 3H:1V$

Rate

2000 lb/acre

2500 lb/acre

