

AA series brass compact actuator



features

- durable brass automatic actuators.
- flow control stem with external bleed screw and 14" lead wires.
- optimal flow: 5-35 GPM.
- rated to 150 PSI, optimal 30-90 PSI.
- solenoid: 24VAC/60Hz; inrush current 0.59 amps (14.2 VA); holding current 0.33 amps (7.9 VA).

base model	AA-075	AA-100	AB-075-B	AB-100-B
description	compact brass 3/4"	compact brass 1"	compact 3/4" boxed	compact 1" boxed
weight (lbs)	1.58	1.66	1.58	1.66
case qty	12	12	12	12

repair & replacement parts

compact actuator rebuild kit	compact actuator rebuild kit	replacement 24VAC solenoid	replacement brass bleed screws
# RK-17C compact actuator rebuild kit (old style)	# RK-18C compact actuator rebuild kit-2017 model	# RK-28C open yoke, 24VAC/60hz, inrush current: 0.33 Amps (7.9 VA) with 14" lead wires	# RK-29C with o-rings. for classic (CL) or compact (AA, AB), or other AV

CL classic brass actuator



base model	CL-075	CL-100	CL-075-B	CL-100-B
description	classic 3/4"	classic 1"	classic 3/4" boxed	classic 1" boxed
weight (lbs)	2.3	2.3	12.3	2.3
case qty	6	6	10	10

repair & replacement parts

classic actuator rebuild kit	classic actuator rebuild kit	replacement 24VAC solenoid	replacement brass bleed screws	classic actuator rebuild kit
# RK-25C pre 2004 models	# RK-26C models installed after 2004 through 2016	# RK-28C open yoke, 24VAC/60hz, inrush current: 0.33 Amps (7.9 VA) with 14" lead wires	# RK-29C with o-rings. for classic (CL) or compact (AA, AB), or other AV	# RK-38C for model installed in 2016 through present. flat diaphragm & external actuator spring