


HB880R


Heavy-Duty 7-Day Outdoor Digital Plug-In Timers

Full feature plug-in timer provides 7-day programming in a weatherproof enclosure with astronomical clock and Daylight Saving Time (DST) adjustment in a convenient plug-in for quick and easy automation.

Features

- 14 ON/OFF programmable events
- Full 7-day programming options, including astronomical clock, automatic DST adjustment, and random mode
- Rainproof, outdoor rated enclosure with two grounded receptacles
- 3-prong plug on a 24" long cord
- Incandescent/fluorescent/CFL/LED compatible
- AA battery backup (included)
- Plugs directly into wall outlet

Model #	Voltage	Rect/Plug
HB880R	15 A, 120 VAC, 60 Hz	5-15 



Ratings	
Operating Voltage	120 VAC, 60 Hz
Resistive	15 A, 120 VAC, 60 Hz
Inductive Ballast	8.3 A, 120 VAC, 60 Hz
Electronic/ LED Ballast	500 VA, 60 Hz
Tungsten/Incandescent	1000 W, 120 VAC, 60 Hz
Motor	1/2 HP, 120 VAC, 60 Hz
Dimensions H x W x D	5 3/8" X 5" X 1 7/8" (137 mm x 129 mm x 48 mm)
Warranty	1-year limited


DT200LT Series

Digital Landscape Timer

Digital 7-day landscape timer with DST, rated for use in low voltage transformers up to 1200W featuring ON programming at Dusk or predetermined time and OFF at Dawn or predetermined time.

Features

- Factory set AUTO DST option takes the hassle out of Daylight Saving Time adjustments
- One push, programming override for homeowner convenience
- Rated for use in low voltage transformers up to 1200 W
- An operating temperature range of -40° F to 122° F (-40° C to 50° C) for steady performance in all types of climates
- Two included LR44 batteries retain the correct time and settings for up to three months without power
- Use with UL Certified Type 3R enclosure (sold separately)
- Intermatic Linesync technology provides accurate timing for years

Model #	Voltage	Rect/Plug
DT200LT	15 A, 120 VAC, 60 Hz	5-15 



Ratings	
Operating Voltage	120 VAC, 60 Hz
Resistive	15 A, 120 VAC, 60 Hz
Inductive Ballast	12 A, 120 VAC, 60 Hz
Tungsten/Incandescent	1000 W, 120 VAC, 60 Hz
Motor	1/2 HP @ 120 VAC, 60 Hz
Dimensions H x W x D	3 3/16" X 3 3/16" X 2 1/4" (81 mm x 84 mm x 57 mm)
Warranty	1-year