

SDS**GHS Safety Data Sheet**
PROFILE Products, LLC**HydroCover® TripleStart™**

MSDS Number: LIM070

Revision Date: 1/15/13

Page 1 of 4

1

PRODUCT AND COMPANY IDENTIFICATION**Manufacturer**

PROFILE Products, LLC
750 LAKE COOK ROAD
SUITE 440
BUFFALO GROVE, IL 60089

Phone: (847) 215-1144
Fax: (847) 215-0577
Email: profileproducts.com
Web: www.profileproducts.com

Product Name: HydroCover® TripleStart™
Revision Date: 1/15/13
MSDS Number: LIM070
CAS Number: Not applicable
Product Use: Erosion control mulch for hydraulic seeding

Product Description: Pellets of green dyed cellulose fibers from shredded waste paper sources

2

HAZARDS IDENTIFICATION

Route of Entry: Inhalation, skin contact, eye contact

Inhalation: Cellulose dust may cause sneezing, irritation, and dryness of the nose and throat. Dust may aggravate pre-existing respiratory conditions.

Skin Contact: Cellulose dust can cause irritation. Skin absorption is not known to occur.

Eye Contact: Cellulose dust can irritate the eyes.

Ingestion: No reports of human ingestion.

OSHA Classification: Cellulose dust is a hazardous substance as defined by the Hazard Communication Standard 29CFR 1910.1200

3

COMPOSITION/INFORMATION ON INGREDIENTS**Ingredients:**

Cas #	Perc.	Chemical Name

SDS**GHS Safety Data Sheet**
PROFILE Products, LLC**HydroCover® TripleStart™**

MSDS Number: LIM070

Revision Date: 1/15/13

Page 2 of 4

4

FIRST AID MEASURES

Inhalation: Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation persists.

Skin Contact: Usually not a problem. Wash off with running water if irritation is experienced.

Eye Contact: Open eyelids and flush with water.

Ingestion: Get medical attention.

5

FIRE FIGHTING MEASURES

Flammability: Combustible product

Flash Point: Not applicable

Flash Point Method: Not applicable

Autoignition Temp: 200-206°C (400-500°F)

Conditions to avoid: In contact with flames or hot surfaces

Flammable- Extinguish with water; same as a wood fire

6

ACCIDENTAL RELEASE MEASURES

Scoop up product. Wear goggles and respirator if dust is produced in unventilated areas. Wet product will be slippery.

7

HANDLING AND STORAGE

Handling Precautions: Clean up areas where dust settles. Minimize blowdown or other practices that generate high airborne dust concentrations.

Storage Requirements: Store in a cool, dry place. Keep away from sources of ignition.

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: None required for outdoor mixing and application. Use dust collection system for indoor handling operations.

Personal Protective Equip: Eye Protection: Wear goggles when emptying bags and during other operations where there is a risk of dust entering the eyes.
Gloves: Leather, plastic or rubber gloves could be worn to minimize skin irritation.
Respirators: When handling methods generate dust at concentrations that exceed occupational exposure limits, wear a NIOSH approved respirator. A fabric respirator or a facepiece respirator with dust cartridges will generally provide adequate protection.
Footwear: The product is slippery when wet. Wear appropriate footwear.

SDS**GHS Safety Data Sheet**
PROFILE Products, LLC**HydroCover® TripleStart™**

MSDS Number: LIM070

Revision Date: 1/15/13

Page 3 of 4

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Dyed, green pellets - Shredded waste paper	Odor:	Mild wood odor
Physical State:	Cellulose Fibers	Solubility:	N/A
Spec Grav./Density:	lighter than water	Freezing/Melting Pt.:	N/A
Boiling Point:	N/A	Vapor Density:	N/A
Vapor Pressure:	N/A		
pH:	N/A		

10 STABILITY AND REACTIVITY

Stability:	Stable product
Conditions to Avoid:	Contact with strong acids and oxidizers may generate heat. Product may ignite at temperatures in excess of 200°C (400°F).
Materials to Avoid:	Strong acids and oxidizers
Hazardous Decomposition:	None Determined
Hazardous Polymerization:	Will not occur.

11 TOXICOLOGICAL INFORMATION**EFFECTS OF CHRONIC EXPOSURE:**

Inhalation: Frequent and repeated exposure to wood dust is associated with an increased risk of developing nasal cancer.
 Skin Contact: Although rare, wood dust may cause dermatitis in sensitized people.

Particulates Not Otherwise Regulated (PNOR): OSHA: PEL-TWA 15 mg/m³ (Total Dust);
 5 mg/m³ (Respirable fraction)

Irritancy: Cellulose could be a mild irritant.
 Sensitization: Some cellulose dusts may cause allergic skin reactions.

12 ECOLOGICAL INFORMATION**13 DISPOSAL CONSIDERATIONS**

Normally can be disposed of as a wood residue. Ensure disposal is in compliance with local, provincial (state), and federal regulations.

14 TRANSPORT INFORMATION

DOT Class: Not regulated #

SDS

GHS Safety Data Sheet

PROFILE Products, LLC



HydroCover® TripleStart™

MSDS Number: LIM070

Revision Date: 1/15/13

Page 4 of 4

15	REGULATORY INFORMATION
----	-------------------------------

COMPONENT / (CAS/PERC) / CODES

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
NRC = Nationally Recognized Carcinogens
OSHA WAC = OSHA workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance
CSWHS = Clean water Act Hazardous substances
EHS302 = Extremely Hazardous Substance
EPCRAWPC = EPCRA Water Priority Chemicals
HAP = Hazardous Air Pollutants
NJEHS = NJ Extraordinarily Hazardous Substances
NJHS = NJ Right-to-Know Hazardous Substances
OSHA PSM = OSHA Chemicals Requiring process safety management
SARA313 = SARA 313 Title III Toxic Chemicals

16	OTHER INFORMATION
----	--------------------------

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.