

HydroCover

TRIPLESTART™
HYDROSEEDER • SPREADER • HAND

**3-IN-1
MULCHING
GRANULES**

Distributed by
John Deere Landscapes
800-347-4272

LFHCTS



PROFILE Products LLC
750 Lake Cook Road, Suite 440 • Buffalo Grove, IL 60089 • 800-726-6371
Manufactured by PROFILE Products LLC • Limestone, TN
www.hydrocovermulch.com

HydroCover®

TRIPLESTART™
HYDROSEEDER • SPREADER • HAND

**3-IN-1
MULCHING
GRANULES**

**HYDROSEEDING
APPLICATION RATES**

Flat to 5H to 1V Slopes 2000 lb/ac (2242 kg/ha)
5H to 1V – 4H to 1V Slopes 2500 lb/ac (2802 kg/ha)
3H to 1V Slopes 3000 lb/ac (3363 kg/ha)
> 3H to 1V Slopes 3500 lb/ac (3923 kg/ha)

**BROADCAST SPREADING
APPLICATION RATES**

Flat to 5H to 1V Slopes 60 lb/1000 sq ft (27 kg/93 sq m)
5H to 1V – 3H to 1V Slopes 80 lb/1000 sq ft (36 kg/93 sq m)
> 3H to 1V Slopes 100 lb/1000 sq ft (45 kg/93 sq m)

Net Weight: 40 lb (18.14 kg)
MADE IN U.S.A.

Distributed by
John Deere Landscapes
800-347-4272

A012-028374-3

Version: TripleStart (Limestone, TN)
Color: 2/color
Pantone 1797 Red and Black
swanson•russell

HydroCover

TRIPLESTART™
HYDROSEEDER • SPREADER • HAND

**3-IN-1
MULCHING
GRANULES**

Distributed by
John Deere Landscapes
800-347-4272

LFHCTS



PROFILE Products LLC
750 Lake Cook Road, Suite 440 • Buffalo Grove, IL 60089 • 800-726-6371
Manufactured by PROFILE Products LLC • Limestone, TN
www.hydrocovermulch.com

HydroCover®

TRIPLESTART™ 3-IN-1
HYDROSEEDER • SPREADER • HAND MULCHING
GRANULES



PRODUCT COMPOSITION/NON PLANT FOOD INGREDIENTS:
58% Cellulose Fiber
37% Wood Fiber
5% Wetting Agents



INSTALLATION GUIDELINES

HYDROSEEDING:
Add 60 pounds (27 kg) of HydroCover® TripleStart™ per 100 gallons (379 L) of water; confirm loading rates with equipment manufacturer.



INSTALLATION INSTRUCTIONS

HYDROSEEDING:
Strictly comply with manufacturer's installation instructions and recommendations. Use approved hydro-spraying machines. Do not exceed maximum slope length of 35 feet (11 m) when slope gradients are steeper than 4H to 1V.

BROADCAST SPREADING:
Strictly comply with manufacturer's installation instructions and recommendations. Use Lesco 36" Drop Spreader with a fixed rate plate. You may also spread by hand for spot or patch seeding. Do not exceed maximum slope length of 25 feet (8 m) when slope gradients are steeper than 4H to 1V.



WARRANTY

PROFILE PRODUCTS LLC ("Profile") represents and warrants that its products are manufactured in accordance with the product's specifications and that its products, at the time of delivery to the purchaser, shall be free from all material defects. In the event of a breach of the foregoing warranty, Profile's sole obligation shall be, at its option, to refund the purchase price or to provide products which conform to this warranty, so long as any deficiencies are reported to Profile within thirty (30) days after discovery thereof, but in no event later than one (1) year after the date of manufacture. ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, BY LAW OR OTHERWISE, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE DISCLAIMED. FURTHER, IT IS UNDERSTOOD AND AGREED THAT PROFILE'S LIABILITY SHALL NOT EXCEED THE RETURN OF THE AMOUNT OF THE PURCHASE PRICE PAID BY PURCHASER AND UNDER NO CIRCUMSTANCES SHALL PROFILE BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR PUNITIVE DAMAGES. Products for which a warranty claim is made are to be returned transportation prepaid to Profile's factory. Any use not in accordance with product directions and precautionary statements, and any modifications or additives to the products, or any adulteration, dilution or alteration by the purchaser shall void this warranty. No employee or representative of Profile is authorized to change this warranty in any way or to grant any other warranty.

Profile and HydroCover are registered trademarks of PROFILE Products LLC.
TripleStart and Solutions for your Environment are trademarks of PROFILE Products LLC.