

2216 Aluminum | 50 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB Std



HOUSING/SHROUD	
2216	<ul style="list-style-type: none"> » Die-cast » Copper-free aluminum » Silicone O-ring gasket » Superior weather-tight seal
2416	<ul style="list-style-type: none"> » Injection-molded, reinforced polymer » Formulated for most Vista polyester powder-coated finishes » Exceptional strength and UV stability » Dual silicone O-ring gaskets » Superior weather-tight seal
FINISH	
<ul style="list-style-type: none"> » Polyester powder-coated finish. See ordering information for available colors. 	
SOCKET/LAMP HOLDER	
<ul style="list-style-type: none"> » Proprietary ceramic socket » Nickel contacts » Stainless steel springs » Teflon-jacketed wire leads 	
LENS	
<ul style="list-style-type: none"> » Clear » Tempered » Shock- and heat-resistant » Soda-lime glass » For optical effect lenses, see ordering information. 	

LAMP TYPE	<ul style="list-style-type: none"> » Standard lamp included with fixture. For other lamp and wattage options see Lamp Guide, pages 128-130.
PHOTOMETRICS	<ul style="list-style-type: none"> » For photometric data, see pages 131-149.
MOUNTING	<ul style="list-style-type: none"> » Adjustable knuckle with 1/2" NPT » Injection-molded, reinforced polymer » Fixture may be mounted into threaded hubs in junction boxes, ground stakes, tree mount boxes, or mounting canopies. » See ordering information for mounting options. For optional mounting accessories, see pages 126-127.
FASTENERS	<ul style="list-style-type: none"> » Stainless steel fasteners
WIRING	<ul style="list-style-type: none"> » Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable.