

2216 Aluminum | 50 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB Std



|  |  |
|--|--|
| HOUSING/SHROUD   |  |
| 2216   | <ul style="list-style-type: none"> <li>» Die-cast</li> <li>» Copper-free aluminum</li> <li>» Silicone O-ring gasket</li> <li>» Superior weather-tight seal</li> </ul>  |
| 2416   | <ul style="list-style-type: none"> <li>» Injection-molded, reinforced polymer</li> <li>» Formulated for most Vista polyester powder-coated finishes</li> <li>» Exceptional strength and UV stability</li> <li>» Dual silicone O-ring gaskets</li> <li>» Superior weather-tight seal</li> </ul> |
| FINISH   |  |
| <ul style="list-style-type: none"> <li>» Polyester powder-coated finish. See ordering information for available colors.</li> </ul> |  |
| SOCKET/LAMP HOLDER   |  |
| <ul style="list-style-type: none"> <li>» Proprietary ceramic socket</li> <li>» Nickel contacts</li> </ul>                          | <ul style="list-style-type: none"> <li>» Stainless steel springs</li> <li>» Teflon-jacketed wire leads</li> </ul>  |
| LENS   |  |
| <ul style="list-style-type: none"> <li>» Clear</li> <li>» Tempered</li> <li>» Shock- and heat-resistant</li> </ul>                 | <ul style="list-style-type: none"> <li>» Soda-lime glass</li> <li>» For optical effect lenses, see ordering information.</li> </ul>  |

|              |   |
|--------------|---|
| LAMP TYPE    | <ul style="list-style-type: none"> <li>» Standard lamp included with fixture. For other lamp and wattage options see Lamp Guide, pages 128-130.</li> </ul>  |
| PHOTOMETRICS | <ul style="list-style-type: none"> <li>» For photometric data, see pages 131-149.</li> </ul>  |
| MOUNTING     | <ul style="list-style-type: none"> <li>» Adjustable knuckle with 1/2" NPT</li> <li>» Injection-molded, reinforced polymer</li> <li>» Fixture may be mounted into threaded hubs in junction boxes, ground stakes, tree mount boxes, or mounting canopies.</li> <li>» See ordering information for mounting options. For optional mounting accessories, see pages 126-127.</li> </ul> |
| FASTENERS    | <ul style="list-style-type: none"> <li>» Stainless steel fasteners</li> </ul>   |
| WIRING       | <ul style="list-style-type: none"> <li>» Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable.</li> </ul>  |