



GATOR BLOCK BOND XP
LOW VOC POLYURETHANE ADHESIVE

SDS Revision Date (dd/mm/yyyy): 27/01/2016

Page 1 of 8



SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product form : aromatic isocyanates
Product name : Gator Block Bond XP
Use of the substance/mixture : Various

Details of the supplier of the safety data sheet

Supplier : Alliance Designer Products Inc.
 225 Blvd Bellerose West
 Laval, Quebec
 Canada
 H7L 6A1
www.alliancegator.com
24 hour Emergency Phone : CHEMTREC (800) 424-9300
 CHEMTREC International +1 (703) 527-3887

SECTION 2 - HAZARDS IDENTIFICATION

Emergency overview

WARNING:

CONTAINS DIPHENYLMETHANE DIISOCYANATE (CAS No. 101-68-8). INHALATION OF MDI MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

State of matter : solid
Colour : tan
Odour : oily, mild

POTENTIAL HEALTH EFFECTS

Primary routes of exposure : Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for sgases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity : May cause sensitization by inhalation.
Irritation / corrosion : Irritating to eyes, respiratory system and skin.
Sensitization : Sensitization after skin contact possible. The substance may cause sensitization of the respiratory tract. Studies in animals suggest that dermal exposure may lead to pulmonary sensitization. However, the relevance of this result for humans is unclear.



**GATOR BLOCK BOND XP
LOW VOC POLYURETHANE ADHESIVE**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 2 - HAZARDS IDENTIFICATION (CONT.)

**Signs and symptoms
of overexposure :**

In sensitized individuals, sensitization reactions may be elicited by structurally similar substances. Respiratory sensitization may result in allergic (asthma-like) signs in the lower respiratory tract including wheezing, shortness of breath and difficulty breathing, the onset of which may be delayed. Repeated inhalation of high concentrations may cause lung damage, including reduced lung function, which may be permanent. Substances eliciting lower respiratory tract irritation may worsen the asthma-like reactions that may be produced by product exposures.

POTENTIAL ENVIRONMENTAL EFFECTS

Aquatic toxicity : The product has not been tested.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

CAS Number	Content (W/W)	Chemical name
14807-96-6	15.0 - 40.0 %	talc
101-68-8	7.0 - 13.0 %	Diphenylmethane-4,4'-diisocyanate (MDI)
64742-46-7	5.0 - 10.0 %	Distillates (petroleum), hydrotreated middle
26447-40-5	3.0 - 7.0 %	Methylenediphenyl diisocyanate
9016-87-9	1.0 - 5.0 %	P-MDI

SECTION 4 - FIRST AID MEASURES

General advice :	Remove contaminated clothing.
If inhaled :	Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.
If on skin :	Wash affected areas thoroughly with soap and water. Consult a doctor if skin irritation persists.
If in eyes :	In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Immediate medical attention required.
If swallowed :	Rinse mouth and then drink plenty of water. Do not induce vomiting. Immediate medical attention required.

NOTE TO PHYSICIAN

Antidote :	Specific antidotes or neutralizers to isocyanates do not exist.
Treatment :	Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.



**GATOR BLOCK BOND XP
LOW VOC POLYURETHANE ADHESIVE**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point : > 200 °F
Flash Point : > 93.34 °C
Autoignition : No data available.
Lower explosion limit : 1.6 %(V)
Upper explosion limit : 10.2 %(V)
Self-ignition temperature : not self-igniting

Suitable extinguishing media : water spray, foam, carbon dioxide
Hazards during fire-fighting : nitrous gases, fumes/smoke, isocyanate, harmful vapours
Protective equipment for fire-fighting : Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Personal precautions : Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.
Environmental precautions : Do not discharge into drains/surface waters/groundwater.

SECTION 7 - HANDLING AND STORAGE

HANDLING

General advice : Avoid contact with the skin, eyes and clothing. Avoid excessive temperatures. Avoid humidity. Avoid aerosol formation.

Protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. If exposed to fire, keep containers cool by spraying with water.

STORAGE

General advice : Keep container tightly closed and in a well-ventilated place.
Storage stability : Storage temperature: 65 - 104 °F
Protect against moisture.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

Diphenylmethane-4,4'-diisocyanate (MDI)	OSHA	CLV 0.02 ppm 0.2 mg/m ³ ;
	ACGIH	TWA value 0.005 ppm ;
talc	OSHA	TWA value 20 millions of particles per cubic foot of air ; TWA value 2.4 millions of particles per cubic foot of air Respirable ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 0.1 mg/m ³ Respirable ;



**GATOR BLOCK BOND XP
LOW VOC POLYURETHANE ADHESIVE**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION (CONT.)

	The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 0.3 mg/m ³ Total dust ;
ACGIH	The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 2 mg/m ³ Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.

Advice on system design : Provide local exhaust ventilation to control vapours/mists.

PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection :	When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place.
Hand protection :	Chemical resistant protective gloves, Protective glove selection must be based on the user's assessment of the workplace hazards.
Eye protection :	Safety glasses with side-shields. Wear face shield if splashing hazard exists.
Body protection :	Body protection must be chosen based on level of activity and exposure.
General safety and hygiene measures :	Wear protective clothing as necessary to prevent contact. Eye wash fountains and safety showers must be easily accessible. Observe the appropriate PEL value. Wash soiled clothing immediately. Contaminated equipment or clothing should be cleaned after each use or disposed of.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form :	paste
Odour :	oily, mild
Colour :	tan
pH value :	neutral to slightly alkaline
Melting point :	not applicable
Vapour pressure :	No data available.
Density :	1.26 g/cm ³
Bulk density :	1.26 g/cm ³
Vapour density :	Heavier than air.
Partitioning coefficient : n-octanol/water (log Pow):	No data available.
Solubility in water :	slightly soluble



GATOR BLOCK BOND XP
LOW VOC POLYURETHANE ADHESIVE

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 10 - STABILITY AND REACTIVITY

Conditions to avoid :	Avoid moisture. Avoid prolonged exposure to extreme heat. Avoid sources of ignition.
Substances to avoid :	water, alcohols, strong bases, oxidizing agents, Substances/products that react with isocyanates.
Hazardous reactions :	The product is chemically stable.
Decomposition products :	Hazardous decomposition products: aromatic isocyanates, gases/vapours, carbon oxides, nitrogen oxides
Oxidizing properties :	Based on its structural properties the product is not classified as oxidizing.

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute toxicity :	Information on: Diphenylmethane-4,4'-diisocyanate (MDI) Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact. Inhalation of vapours may cause irritation of the mucous membranes of the nose, throat or trachea, breathlessness, chest discomfort, difficult breathing and reduced pulmonary function. Inhalation exposure well above the PEL may result additionally in eye irritation, headache, chemical bronchitis, asthma-like findings or pulmonary edema. Isocyanates have also been reported to cause hypersensitivity pneumonitis, which is characterized by flu-like symptoms, the onset of which may be delayed. Gastrointestinal symptoms include nausea, vomiting and abdominal pain.
Oral :	No data available.
Inhalation :	No data available.
Dermal :	No data available.
Irritation / corrosion :	Information on: Distillates (petroleum), hydrotreated middle Assessment of irritating effects: May cause slight irritation to the skin. Not irritating to the eyes. Information on: Diphenylmethane-4,4'-diisocyanate (MDI) Assessment of irritating effects: Irritating to eyes, respiratory system and skin. Information on: Methylenediphenyl diisocyanate Assessment of irritating effects: Irritating to eyes and skin. Information on: P-MDI Assessment of irritating effects: Irritating to eyes, respiratory system and skin.
Sensitization :	Information on: Diphenylmethane-4,4'-diisocyanate (MDI) Assessment of sensitization: The substance may cause sensitization of the respiratory tract. Sensitization after skin contact possible. Studies in animals suggest that dermal exposure may lead to pulmonary sensitization. However, the relevance of this result for humans is unclear. As a result of previous repeated overexposures or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the PEL/TLV. These symptoms, which include chest tightness, wheezing, cough, shortness of breath, or asthmatic attack, could be immediate or delayed up to several hours after exposure. Similar to many non-specific asthmatic responses, there are reports that once sensitized an individual can experience these symptoms upon exposure to dust, cold air, or other irritants. This increased lung sensitivity can persist for weeks and in severe cases for several years.



**GATOR BLOCK BOND XP
LOW VOC POLYURETHANE ADHESIVE**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 11 - TOXICOLOGICAL INFORMATION (CONT.)

Chronic overexposure to isocyanates has also been reported to cause lung damage, including a decrease in lung function, which may be permanent. Prolonged contact can cause reddening, swelling, rash, scaling, or blistering. In those who have developed a skin sensitization, these symptoms can develop as a result of contact with very small amounts of liquid material, or even as a result of vapour-only exposure.

Information on: Methylenediphenyl diisocyanate Assessment of sensitization: The substance may cause sensitization of the respiratory tract. Sensitization after skin contact possible.

Information on: P-MDI Assessment of sensitization: The substance may cause sensitization of the respiratory tract. Sensitization after skin contact possible.

Carcinogenicity :

Information on: Diphenylmethane-4,4'-diisocyanate (MDI) A carcinogenic potential cannot be excluded after prolonged exposure to severely irritating concentrations. These effects are not relevant to humans at occupational levels of exposure.

Information on: P-MDI Based on the ingredients there is a suspicion of a carcinogenic effect in humans.

SECTION 12 - ECOLOGICAL INFORMATION

Other adverse effects :

Do not release untreated into natural waters. Do not allow to enter soil, waterways or waste water channels. The product has not been tested. The statement has been derived from the properties of the individual components.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste disposal of substance :

Incinerate or dispose of in a licensed facility. Observe all local regulations.

Container disposal :

Do not reuse empty containers.

SECTION 14 - TRANSPORT INFORMATION

Land transport

USDOT :

Not classified as a dangerous good under transport regulations

Sea transport

IMDG :

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO :

Not classified as a dangerous good under transport regulations



Alliance Designer Products Inc.

225 Blvd. Bellerose West, Laval, Quebec, Canada H7L 6A1
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.alliancegator.com - Email : info@alliancegator.com



**GATOR BLOCK BOND XP
LOW VOC POLYURETHANE ADHESIVE**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 15 - REGULATORY INFORMATION

FEDERAL REGULATIONS

Registration status :

Chemical TSCA, US released / listed

OSHA hazard category : IARC 1, 2A or 2B carcinogen; Chronic target organ effects reported; OSHA PEL established; ACGIH TLV established

EPCRA 311/312

(Hazard categories) : Acute; Chronic

STATE REGULATIONS

State RTK	CAS Number	Chemical name
MA, NJ, PA	14807-96-6	talc
MA, NJ, PA	101-68-8	Diphenylmethane-4,4'-diisocyanate (MDI)
MA, NJ, PA	64742-46-7	Distillates (petroleum), hydrotreated middle
MA, NJ, PA	9016-87-9	P-MDI

SECTION 16 - OTHER INFORMATION

HMIS III rating

Health: 2 3 Flammability: 1 Physical hazard: 1

NFPA and HMIS use a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates extreme danger. Although similar, the two rating systems are intended for different purposes, and use different criteria. The NFPA system was developed to provide an on-the-spot alert to the hazards of a material, and their severity, to emergency responders. The HMIS system was designed to communicate workplace hazard information to employees who handle hazardous chemicals.

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.



GATOR BLOCK BOND XP
LOW VOC POLYURETHANE ADHESIVE
SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 16 -OTHER INFORMATION (CONT.)

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. END OF DATA SHEET