



GATOR CLEAN
GATORENE
TDS Revision Date (dd/mm/yyyy): 25/04/2014



Technical Data Sheet

UPDATE: April 1, 2014
Make sure you have an updated data sheet on hand.
Canada and U.S. dial **1-855-847-7767** or (450) 624-1611

DESCRIPTION: GATORENE is ideal for removing, retouching & restoring water & solvent-based sealers. GATORENE will also remove certain adhesives, and is an excellent clean-up solvent for tools and equipment immediately after use. Not intended for sale or use in California. It is also great for clean up and flushing of sealers, metal sprayers.

FOR USE ON:

- Degreasing and cleaning tools
- Thinning specialty coatings
- Flushing metal sprayers

<u>PACKAGING:</u>	Product	Size	per Box	per Pallet
	Gator Clean Gatorene	3.78 L (1 U.S. gal.)	4 units	24 boxes

LIMITED WARRANTY:

ALLIANCE DESIGNER PRODUCTS INC. cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation of **ALLIANCE DESIGNER PRODUCTS INC.** is to refund the purchase price. Proof of purchase is required for any claim. **ALLIANCE DESIGNER PRODUCTS INC.** shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, **ALLIANCE DESIGNER PRODUCTS INC.** excludes any implied warranty of quality, merchantability or fitness for purpose.


DANGER:

FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. SKIN IRRITANT. READ CAREFULLY OTHER CAUTIONS ON THE SIDE PANELS.

CONTENTS MAY CATCH FIRE. FUMES MAY CATCH FIRE. CONTENTS ARE HARMFUL. FUMES ARE HARMFUL. MAY IRRITATE EYES. MAY IRRITATE SKIN. Do not smoke. Do not swallow. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Keep out of reach of children. Wear rubber gloves. Use only in a well-ventilated area or use an organic vapor respirator. Keep away from flames, such as a pilot light and any object that sparks, such as an electric motor. To open - push cap down and turn counter-clockwise. To close - push cap down and turn clockwise until tight. **FIRST AID TREATMENT:** Contains Xylene. If swallowed, call a Poison Control Centre or doctor immediately. If person is alert, do not induce vomiting; product could be aspirated into lungs. If in eyes, rinse with water for 20 minute. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.



DANGER
POISON IRRITANT FLAMMABLE



SEE THE INSTALLATION VIDEO
ON ALLIANCEGATOR.COM