



LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and

Regulations Revision Date: 03/09/2021 Date of issue: 07/02/2013

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer

Product Code: EPA Registration No.: 10404-88 (0.20%); 10404-113 (0.20%); 10404-89 (0.43%); 10404-90 (0.68%); 10404-91 (2.0%); 60063-28-10404 (0.29%); 60063-41-10404 (0.29%); 60063-40-10404 (0.37%); 10404-114 (0.37%)

Synonyms: Dinitroaniline Herbicide; N3,N3-Di-n-propyl-2,4-dinitro-6-(trifluoromethyl)-m-phenylenediamine

Other means of identification: LESCO Stonewall® Pre-emergence Herbicide plus Fertilizer; LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer

1.2. Intended Use of the Product

Use of the substance/mixture: Pesticide & Fertilizer

1.3. Name, Address, and Telephone of the Responsible Party

Company

LESCO, Inc.

1385 East 36th St

Cleveland, OH 44114

T 800-347-4272

1.4. Emergency Telephone Number

Emergency Number : 1-800-424-9300

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Accident, call CHEMTREC – Day or Night

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Acute Tox. 4 (Oral) H302

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Skin Sens. 1 H317

STOT SE 3 H335

Aquatic Acute 3 H402

Aquatic Chronic 3 H412

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



GHS07

Signal Word (GHS-US)

: Warning

Hazard Statements (GHS-US)

: H302 - Harmful if swallowed

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H402 - Harmful to aquatic life

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements (GHS-US)

: P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P264 - Wash exposed areas thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P272 - Contaminated work clothing should not be allowed out of the workplace

P273 - Avoid release to the environment

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER/doctor/physician if you feel unwell
P321 - Specific treatment (see Section 4)
P330 - If swallowed, rinse mouth
P332+P313 - If skin irritation occurs: Get medical advice/attention
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P362+P364 - Take off contaminated clothing and wash it before reuse
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up
P501 - Dispose of contents/container according to local, state, national and international regulations.

2.3. Other Hazards

Other Hazards Not Contributing to the Classification: No additional information available

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Urea	(CAS No) 57-13-6	0.1 - 98	Not classified
Sulfuric acid, dipotassium salt	(CAS No) 7778-80-5	0.1 - 95	Not classified
Diammonium phosphate	(CAS No) 7783-28-0	0.1 - 95	Skin Irrit. 2, H315 Eye Irrit. 2B, H320 STOT SE 3, H335 Aquatic Acute 3, H402
Potassium chloride	(CAS No) 7447-40-7	0.1 - 95	Eye Irrit. 2B, H320
Monoammonium phosphate	(CAS No) 7722-76-1	0.1 - 95	Skin Irrit. 2, H315 Eye Irrit. 2B, H320 STOT SE 3, H335
Ammonium sulfate	(CAS No) 7783-20-2	0.1 - 95	Aquatic Acute 2, H401
Limestone	(CAS No) 1317-65-3	0.1 - 95	Not classified
Sulfur	(CAS No) 7704-34-9	0.1 - 20	Comb. Dust Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Aquatic Acute 3, H402
Iron oxide (Fe ₂ O ₃)	(CAS No) 1309-37-1	0.1 - 10	Not classified
Urea, polymer with formaldehyde	(CAS No) 9011-05-6	0.1 - 10	Not classified
Kaolin	(CAS No) 1332-58-7	0.1 - 10	Not classified
Magnesium sulfate	(CAS No) 7487-88-9	0.1 - 10	Skin Sens. 1, H317

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
Ferrous sulfate	(CAS No) 7720-78-7	0.1 - 10	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400
Manganese oxide (Mn3O4)	(CAS No) 1317-35-7	0.1 - 10	Not classified
Sulfate of Potash-Magnesia	(CAS No) 14977-37-8	0.1 - 10	Not classified
Carbonic acid, magnesium salt (1:1), mixture with magnesium hydroxide (Mg(OH)2), hydrate	(CAS No) 39409-82-0	0.1 - 10	Not classified
1,3-Benzenediamine, 2,6-dinitro-N1,N1-dipropyl-4-(trifluoromethyl)-	(CAS No) 29091-21-2	0.2 - 2	Not classified
Sodium sulfite	(CAS No) 7757-83-7	0.1 - 1	Not classified

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: If medical advice is needed, have product container or label at hand. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). If exposed or concerned: Get medical advice/attention.

First-aid Measures After Inhalation: If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash skin thoroughly with mild soap and water. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation persists.

First-aid Measures After Ingestion: Rinse mouth. If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label. Call a POISON CENTER/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: Harmful if swallowed. Eye irritation. Causes skin irritation. May cause an allergic reaction in sensitive individuals. May cause respiratory irritation.

Symptoms/Injuries After Inhalation: Irritating to the respiratory system and mucous membranes. May cause drowsiness or dizziness.

Symptoms/Injuries After Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation.

Symptoms/Injuries After Ingestion: Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Alcohol foam, dry chemical, carbon dioxide, water spray, fog. Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use water jet. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but will burn at high temperatures. Decomposes above 132 °C (270 °F). Under conditions of fire this material may produce: Ammonia. Nitrogen oxides.

Explosion Hazard: May form explosive compounds if mixed with: Calcium hypochlorite. Sodium hypochlorite. Nitrates. Nitric acid. Perchloric acid. Product itself is not explosive but if dust is generated, dust clouds suspended in air can be explosive.

Reactivity: This product as shipped in the form of coarse granules should not contain sufficient dust to present an explosion hazard. Prevent dust accumulation (to minimize explosion hazard).

5.3. Advice for Firefighters

Firefighting Instructions: Not flammable. Exercise caution when fighting any chemical fire.

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection During Firefighting: Firefighters must use full bunker gear including NIOSH-approved positive-pressure self-contained breathing apparatus to protect against potential hazardous combustion and decomposition products.

Other information: Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Handle in accordance with good industrial hygiene and safety practice. This material becomes slippery when wet. Avoid all eyes and skin contact and do not breathe vapor and mist. Do not allow product to spread into the environment.

6.1.1. For Non-emergency Personnel

Protective Equipment: Wear suitable protective clothing, gloves and eye/face protection. Use appropriate personal protection equipment (PPE).

Emergency Procedures: Collect as any solid. Ventilate area. Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Wear suitable protective clothing, gloves and eye/face protection. Equip cleanup crew with proper protection. Use appropriate personal protection equipment (PPE).

Emergency Procedures: If possible, stop flow of product. Contain and collect as any solid. Evacuate unnecessary personnel. Ventilate area.

6.2. Environmental Precautions

Avoid release to the environment. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain and collect as any solid. Do not allow into drains or water courses or dispose of where ground or surface waters may be affected.

Methods for Cleaning Up: Recover the product by vacuuming, shovelling or sweeping. Avoid generation of dust during clean-up of spills. If spilled directly onto the ground, remove sufficient soil to ensure material is fully recovered. Material may be used if uncontaminated. Clear up spills immediately and dispose of waste safely.

6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: This material becomes slippery when wet.

Precautions for Safe Handling: Handle in accordance with good industrial hygiene and safety procedures. Wear recommended personal protective equipment. Avoid creating or spreading dust. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area.

Hygiene Measures: Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure. Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Wash hands and forearms thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Keep container closed when not in use.

Incompatible Products: Strong acids. Strong bases. Strong oxidizers.

Prohibitions on mixed storage: Store away from: Ammonium nitrate. Refer to Section 10 on Incompatible Materials.

Special Rules on Packaging: Corrosive to copper and its alloys.

7.3. Specific End Use(s)

Fertilizer.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

Limestone (1317-65-3)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Iron oxide (Fe ₂ O ₃) (1309-37-1)		
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
USA IDLH	US IDLH (mg/m ³)	2500 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³

Kaolin (1332-58-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³

8.2. Exposure Controls

Appropriate Engineering Controls

: Ensure all national/local regulations are observed.

Personal Protective Equipment

: Gloves. Safety glasses. Protective clothing. Insufficient ventilation: wear respiratory protection.



Hand Protection

: protective gloves.

Eye Protection

: Chemical goggles or safety glasses.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Granules. Multi-colored
Odor	: Bland
Odor Threshold	: No data available
pH	: No data available
pH solution	: 10 %
Relative Evaporation Rate (butylacetate=1)	: No data available
Melting Point	: 133 °C (271.4°F) Urea
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20 °C	: No data available
Relative Density	: No data available
Density	: 56 (56 - 60) lb/ft ³
Solubility	: Water: Partially soluble
Partition coefficient: n-octanol/water	: No data available
Viscosity	: No data available

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

- 10.1 Reactivity:** This product as shipped in the form of coarse granules should not contain sufficient dust to present an explosion hazard. Prevent dust accumulation (to minimize explosion hazard).
- 10.2 Chemical Stability:** Stable at standard temperature and pressure.
- 10.3 Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4 Conditions to Avoid:** Protect from moisture. Keep away from heat. Direct sunlight. Extremely high or low temperatures. Sparks, heat, open flame and other sources of ignition.
- 10.5 Incompatible Materials:** Strong oxidizers. Strong bases.
- 10.6 Hazardous Decomposition Products:** Under conditions of fire this material may produce: Nitrogen oxides. Ammonia. Carbon oxides (CO, CO₂). Formaldehyde.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity: Harmful if swallowed.

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer	
LD50 Dermal Rat	mg/kg
Sulfuric acid, dipotassium salt (7778-80-5)	
LD50 Oral Rat	6600 mg/kg
Diammonium phosphate (7783-28-0)	
LD50 Oral Rat	6500 mg/kg
LD50 Dermal Rabbit	> 7950 mg/kg
Potassium chloride (7447-40-7)	
LD50 Oral Rat	2600 mg/kg
Monoammonium phosphate (7722-76-1)	
LD50 Oral Rat	5750 mg/kg
LD50 Dermal Rabbit	> 7940 mg/kg
Ammonium sulfate (7783-20-2)	
LD50 Oral Rat	2000 mg/kg
Sulfur (7704-34-9)	
LD50 Oral Rat	> 3000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat (mg/l)	> 9.23 mg/l/4h
Iron oxide (Fe ₂ O ₃) (1309-37-1)	
LD50 Oral Rat	> 10000 mg/kg
Urea, polymer with formaldehyde (9011-05-6)	
LC50 Inhalation Rat (mg/l)	> 167 mg/m ³ (Exposure time: 4 h)
Sodium sulfite (7757-83-7)	
LD50 Oral Rat	3560 mg/kg
LC50 Inhalation Rat (mg/l)	> 22 mg/l (Exposure time: 1 h)
Ferrous sulfate (7720-78-7)	
LD50 Oral Rat	237 mg/kg
1,3-Benzenediamine, 2,6-dinitro-N1,N1-dipropyl-4-(trifluoromethyl)- (29091-21-2)	
LD50 Oral Rat	5050 mg/kg
LD50 Dermal Rat	5050 mg/kg
LC50 Inhalation Rat (ppm)	0.231 ppm
Urea (57-13-6)	
ATE (Oral)	8471.000 mg/kg

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Iron oxide (Fe₂O₃) (1309-37-1)	
IARC group	3

Sodium sulfite (7757-83-7)	
IARC group	3

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Potential Adverse Human Health Effects and Symptoms: Harmful if swallowed.

Symptoms/Injuries After Inhalation: Irritating to the respiratory system and mucous membranes. May cause drowsiness or dizziness.

Symptoms/Injuries After Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation.

Symptoms/Injuries After Ingestion: Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Harmful to aquatic life with long lasting effects.

Sulfuric acid, dipotassium salt (7778-80-5)	
LC50 Fish 1	653 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
EC50 Daphnia 1	890 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	2900 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
LC 50 Fish 2	3550 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

Diammonium phosphate (7783-28-0)	
LC50 Fish 1	26.5 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
LC 50 Fish 2	24.8 - 29.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

Potassium chloride (7447-40-7)	
LC50 Fish 1	1060 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	825 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	2500 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
LC 50 Fish 2	750 - 1020 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

Ammonium sulfate (7783-20-2)	
LC50 Fish 1	5.2 (5.2 - 8.2) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	32.2 (32.2 - 41.9) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

Sulfur (7704-34-9)	
LC50 Fish 1	866 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
LC 50 Fish 2	14 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

Magnesium sulfate (7487-88-9)	
LC50 Fish 1	2610 - 3080 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	266.4 - 417.3 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 Other Aquatic Organisms 1	2700 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)

Ferrous sulfate (7720-78-7)	
LC50 Fish 1	925 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
EC50 Daphnia 1	152 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	0.56 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EC50 Daphnia 2	6.15 - 9.26 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Urea (57-13-6)	
LC50 Fish 1	16200 - 18300 mg/l (Exposure time: 96 h - Species: Poecilia reticulata)
EC50 Daphnia 1	3910 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

12.2. Persistence and Degradability

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer	
Persistence and Degradability	May cause long-term adverse effects in the environment. This product is water soluble and eventually biodegrades into elemental nitrogen. Excess nitrogen and nitrates in a body of water will contribute to eutrophication with visible effects such as toxic algae bloom. . Not established.

12.3. Bioaccumulative Potential

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer	
Bioaccumulative Potential	Not established.
Diammonium phosphate (7783-28-0)	
BCF fish 1	(no bioaccumulation expected)
Monoammonium phosphate (7722-76-1)	
BCF fish 1	(no bioaccumulation expected)
Ammonium sulfate (7783-20-2)	
Log Pow	-5.1 (at 25 °C)
Sodium sulfite (7757-83-7)	
Log Pow	-4 (at 25 °C)
Urea (57-13-6)	
BCF fish 1	< 10
Log Pow	-1.59 (at 25 °C)

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Treatment Methods: Pesticide: Wastes resulting from the use of this product that cannot be used or chemically reprocessed should be disposed of in a landfill approved for pesticide disposal or in accordance with applicable Federal, State or local procedures. Or call (1-800-CLEANUP) for disposal instructions. Never place unused product down any indoor or outdoor drain. Container: Do not reuse bag. Dispose of emptied bag(s) in a sanitary landfill approved for pesticide disposal, or by incineration.

Additional Information: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Ecology – Waste Materials: This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT Not regulated for transport

14.2 In Accordance with IMDG Not regulated for transport

14.3 In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer	
EPA TSCA Regulatory Flag	This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label.
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sulfuric acid, dipotassium salt (7778-80-5)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Diammonium phosphate (7783-28-0)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Potassium chloride (7447-40-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Monoammonium phosphate (7722-76-1)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Ammonium sulfate (7783-20-2)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Sulfur (7704-34-9)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Limestone (1317-65-3)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Iron oxide (Fe₂O₃) (1309-37-1)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Urea, polymer with formaldehyde (9011-05-6)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Kaolin (1332-58-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Sodium sulfite (7757-83-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Magnesium sulfate (7487-88-9)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Ferrous sulfate (7720-78-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Manganese oxide (Mn₃O₄) (1317-35-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
1,3-Benzenediamine, 2,6-dinitro-N1,N1-dipropyl-4-(trifluoromethyl)- (29091-21-2)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Urea (57-13-6)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2 US State Regulations

Potassium chloride (7447-40-7)
U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Monoammonium phosphate (7722-76-1)
U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Ammonium sulfate (7783-20-2)
U.S. - California - SCAQMD - Toxic Air Contaminants With Proposed Risk Values U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728) RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List RTK - U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus

Fertilizer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sulfur (7704-34-9)

RTK - U.S. - Massachusetts - Right To Know List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Mexico - Air Quality - Ambient Air Quality Standards
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Limestone (1317-65-3)

U.S. - Idaho - Occupational Exposure Limits - TWAs
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Oregon - Permissible Exposure Limits - TWAs
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELS
U.S. - Washington - Permissible Exposure Limits - TWAs

Iron oxide (Fe₂O₃) (1309-37-1)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELS
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Urea, polymer with formaldehyde (9011-05-6)

U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Kaolin (1332-58-7)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus

Fertilizer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELS
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Sodium sulfite (7757-83-7)

U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Magnesium sulfate (7487-88-9)

U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Ferrous sulfate (7720-78-7)

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Polluting Materials List
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Manganese oxide (Mn3O4) (1317-35-7)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus

Fertilizer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - North Carolina - Control of Toxic Air Pollutants
 RTK - U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Tennessee - Occupational Exposure Limits - TWAs
 U.S. - Vermont - Permissible Exposure Limits - TWAs
 U.S. - Washington - Permissible Exposure Limits - STELS
 U.S. - Washington - Permissible Exposure Limits - TWAs

Urea (57-13-6)

U.S. - Minnesota - Hazardous Substance List
 U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 05/15/2014
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Acute Tox. Not classified (Oral)	Acute toxicity (oral) Not classified
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Comb. Dust	Combustible Dust
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
	May form combustible dust concentrations in air
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H320	Causes eye irritation
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

NFPA Health Hazard


: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA Fire Hazard

: 1 - Must be preheated before ignition can occur.

NFPA Reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability

: 1 Slight Hazard

Physical

: 0 Minimal Hazard

LESCO Stonewall® (0.20%, 0.29%, 0.37%, 0.43%, 0.68%, 2.0%) Plus Fertilizer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IMPORTANT: The information contained herein is based on available data. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof; and you should make your investigation to determine safety for the use you contemplate. LESCO makes no warranty of merchantability of fitness for a particular use, nor is there any other express or implied warranty except as may be specifically provided otherwise on product. LESCO, Inc. assumes no responsibility or liability for any incidental or consequential damages whether related to personal injury or property damage, to vendees, users or third parties, caused by the material and LESCO's responsibility is limited to replacement of, or repayment of, the purchase price for the material(s) with respect to which any damages are claimed. All vendees or users assume all risk associated with the use of the material(s).

SDS US (GHS HazCom) - US Only 10 pt 2