


MR STANDARD PREMIUM



Long Shroud

| Fixture | Lamp | | Shroud Option | Finish |
|-----------|-----------|---------|-------------------------------------------|----------------|
| MR | NL | No Lamp | [blank] 1" (25 mm) Straight Shroud | CU NP** |
| | | | LS 45° Angled Long Shroud | |

ORDERING EXAMPLE: ▶ **MR-NL-LS-CU** = FIXTURE-LAMP-SHROUD OPTION-FINISH

°Includes Super Slot Spike (753900)

Dimensions

Height: 7.4" (188 mm)
 Diameter: 2.2" (56 mm)
 Lamp: MR-11
 Lead: 10' (3 m)
 Material: Copper/Brass

ACCESSORIES: Specify Separately

| Name | Code | Name | Code | Name | Code |
|------------|--------------------|----------------------------|---------------------|-------------------------|---------------------|
| Post Mount | PM-XX** | Copper Riser with Fittings | YY-R-GT-XX** | ProAim Ratcheting Spike | PARS |
| VersaBox | VB-050-XX** | Gutter Mount | GM-SS | Solite Spread (MR-11) | 250015420000 |
| SJ-Box | SJ-XX** | Hex Baffle (MR-11) | 250015250000 | Frosted Lens (MR-11) | 250010480000 |



LR STANDARD PREMIUM



Long Shroud

| Fixture | Lamp | | Shroud Option | Finish |
|------------|-----------------|------------------------------------------------|---------------------------------------------|----------------|
| LR° | NL | No Lamp | [blank] 1.5" (38 mm) Straight Shroud | CU NP** |
| | LED20WFL | 261 Lumen Lamp 4.0W/4.3VA | LS 45° Angled Long Shroud | |
| | LED35WFL | 337 Lumen Lamp 5.0W/5.4VA | | |
| | LED50WFL | 447 Lumen Lamp 6.0W/6.5VA | | |
| | ZD35WFL | 337 Lumen Lamp 5.0W/5.4VA Zone/Dim with Luxor® | | |

ORDERING EXAMPLE: ▶ **LR-LED20WFL-CU** = FIXTURE-LAMP-FINISH

°Includes Super Slot Spike (753900)

Dimensions

Height: 8.3" (211 mm)
 Diameter: 2.5" (64 mm)
 Lamp: MR-16
 Lead: 10' (3 m)
 Material: Copper/Brass

ACCESSORIES: Specify Separately

| Name | Code | Name | Code | Name | Code |
|--------------|--------------------|----------------------------|----------------------|-------------------------|---------------------|
| Post Mount | PM-XX** | Copper Riser with Fittings | YYΔ-R-GT-XX** | ProAim Ratcheting Spike | PARS |
| VersaBox | VB-050-XX** | Gutter Mount | GM-SS | Solite Spread (MR-16) | 250015240000 |
| Ground Mount | GM-XX** | Hex Baffle (MR-16) | 250015260000 | Frosted Lens (MR-16) | 250015170000 |



Metal



+ Non-returnable * May require longer lead time ** Finish code * Total delivered lumens