

PRO-SPEC EMITTERS

FEATURES

- Fully pressure-compensating zero flush design delivers uniform flow throughout a wide pressure range (5 – 65 psi), regardless of elevation changes and pressure inconsistencies
- Optional Trucheck™ models (PST-CV) include positive internal check spring to hold back 9.25' (2,77 m) of elevated water
- ½" FIPT (PST) or ¼" barbed base (PS) configuration to handle every design situation
- Available in color-coded flow rates of 0.5, 1, 2 and 4 gph, or camouflage colors of desert, granite or mulch
- Flow rate and flow direction are clearly molded into diffuser cap
- Manufactured from UV-inhibited engineering grade plastics – rugged design ensures maximum life span
- Barbed emitters are compatible with PVC or polyethylene tubing. ½" FIPT are compatible with all standard ½" MIPT fittings.



SLV-PST-1 (Threaded)

OPERATING RANGE

PC Flow: 0.5 – 4 gph
 Pressure: 5 – 65 psi
 Filtration: 100-150 mesh

¼" Barbed

WITHOUT TRUCHECK	FLOW RATE	COLOR	INLET
SLV-PS-05	½ gph	Brown	Barbed
SLV-PS-1	1 gph	Black	Barbed
SLV-PS-2	2 gph	Green	Barbed
SLV-PS-4	4 gph	Red	Barbed
SLV-PSG-05	½ gph	Granite Camo	Barbed
SLV-PSG-1	1 gph	Granite Camo	Barbed
SLV-PSG-2	2 gph	Granite Camo	Barbed
SLV-PSG-4	4 gph	Granite Camo	Barbed
SLV-PSD-05	½ gph	Desert Camo	Barbed
SLV-PSD-1	1 gph	Desert Camo	Barbed
SLV-PSD-2	2 gph	Desert Camo	Barbed
SLV-PSD-4	4 gph	Desert Camo	Barbed
SLV-PSM-05	½ gph	Mulch Camo	Barbed
SLV-PSM-1	1 gph	Mulch Camo	Barbed
SLV-PSM-2	2 gph	Mulch Camo	Barbed
SLV-PSM-4	4 gph	Mulch Camo	Barbed
SLV-PSR-05	½ gph	Non-Potable Purple	Barbed
SLV-PSR-1	1 gph	Non-Potable Purple	Barbed
SLV-PSR-2	2 gph	Non-Potable Purple	Barbed
SLV-PSR-4	4 gph	Non-Potable Purple	Barbed

½" Threaded

WITHOUT TRUCHECK	WITH TRUCHECK	FLOW RATE	COLOR	INLET
SLV-PST-05	SLV-PST-CV-05	½ gph	Brown	½" FIPT
SLV-PST-1	SLV-PST-CV-1	1 gph	Black	½" FIPT
SLV-PST-2	SLV-PST-CV-2	2 gph	Green	½" FIPT
SLV-PST-4	SLV-PST-CV-4	4 gph	Red	½" FIPT
SLV-PSTG-05	SLV-PSTG-CV-05	½ gph	Granite Camo	½" FIPT
SLV-PSTG-1	SLV-PSTG-CV-1	1 gph	Granite Camo	½" FIPT
SLV-PSTG-2	SLV-PSTG-CV-2	2 gph	Granite Camo	½" FIPT
SLV-PSTG-4	SLV-PSTG-CV-4	4 gph	Granite Camo	½" FIPT
SLV-PSTD-05	SLV-PSTD-CV-05	½ gph	Desert Camo	½" FIPT
SLV-PSTD-1	SLV-PSTD-CV-1	1 gph	Desert Camo	½" FIPT
SLV-PSTD-2	SLV-PSTD-CV-2	2 gph	Desert Camo	½" FIPT
SLV-PSTD-4	SLV-PSTD-CV-4	4 gph	Desert Camo	½" FIPT
SLV-PSTM-05	SLV-PSTM-CV-05	½ gph	Mulch Camo	½" FIPT
SLV-PSTM-1	SLV-PSTM-CV-1	1 gph	Mulch Camo	½" FIPT
SLV-PSTM-2	SLV-PSTM-CV-2	2 gph	Mulch Camo	½" FIPT
SLV-PSTM-4	SLV-PSTM-CV-4	4 gph	Mulch Camo	½" FIPT
SLV-PSTR-05	SLV-PSTR-CV-05	½ gph	Non-Potable Purple	½" FIPT
SLV-PSTR-1	SLV-PSTR-CV-1	1 gph	Non-Potable Purple	½" FIPT
SLV-PSTR-2	SLV-PSTR-CV-2	2 gph	Non-Potable Purple	½" FIPT
SLV-PSTR-4	SLV-PSTR-CV-4	4 gph	Non-Potable Purple	½" FIPT



DOWNLOAD TECH SPECS AT:
www.salcoirrigation.com