

DRIP FITTINGS AND ACCESSORIES

Insert Barb Fittings

- Made from rigid Acetal material
- Double barb for stronger retention
- Fits 18mm OD (5/8" ID) DL2000 and Drip In



Specifying Information—
Insert Fittings for Drip In & DL2000 Dripline

Model	Description
1620-C	Insert Coupling
1620-E	Insert Elbow
1620-T	Insert Tee
1620-M50	1/2" MPT Adapter



T-YD-500-34 T-FCH-H-FIPT T-FPG02 T-FCH-H-FHT



T-FJQ16 T-IPS1500 T-SS6-50 T-DL-MP9



T-FCC0400 T-FTT0400 T-FEE0400 T-FCV-BB



T-FMP08 T-IPS0104

Specifying Information Accessories

Model	Description
T-YD-500-34	Air Vent—1/2" MIPT Air Release & Vacuum Relief Valve
T-FCH-H-FIPT	Flush Valve—3/4" FPT (Pipe Thread), 0.8 gpm, 2 psi Sealing Pressure
T-FCH-H-FHT	Flush Valve—3/4" FHT (Hose Thread), 0.8 gpm, 2 psi Sealing Pressure
T-DL-MP9	DL2000 Pop-up Operation Indicator
T-FJQ16	5/8" Figure-eight End Clamp
T-SS6-50	3/4" Steel Soil Staple to Hold Tubing in Place
T-IPS1500	5/8" Plastic Stake to Hold Tubing in Place
T-FPG02	Double-sided Goof Plug
T-CA-710	OD Compression Adapter 1/2" Spigot
T-CEFCH-H	OD Compression Adapter with Flush Valve, 0.8 gpm, 2 psi Sealing
T-FMP16	Stainless Steel Insertion Tool for 1/4" Barbed Fittings and Emitters

Specifying Information—Microline 1/4" Fittings

Model	Description
T-FTT0400	Tee (Barb x Barb)
T-FEE0400	Elbow (Barb x Barb)
T-FCC0400	Coupling (Barb x Barb)
T-FCV-BB	Microflow Valve (Barb x Barb)
T-FMP08	Hose Punch for 1/4" barbed fittings and emitter
T-IPS0104	1/4" plastic locator stake to hold tubing in place

Specifying Information—0.710 OD Compression Fittings

Model	Description
T-CA-710	OD Compression Adapter 1/2" Spigot
T-CEFCH-H	OD Compression Adapter with Flush Valve, 0.8 gpm, 2 psi Sealing