

SD DESIGNER PLUS



Fixture	Luxor Option	LED Configuration	Finish
SD [◊]	[blank] Zone	3LED 202 Lumens* 4.2W/4.5VA	BZ DG WI SB FB WG** FW** AL** SV**
	ZD Zone/Dim	6LED 367 Lumens* 8.2W/9.7VA	
		9LED 398 Lumens* 10.0W/10.7VA	
	ZDC [◊] Zone/Dim/ Color	[blank] ZDC with 174 Lumens* 9.1W/11.0VA	

ORDERING EXAMPLE: ▶ SD-ZD-3LED-FB = FIXTURE-LUXOR OPTION-FINISH

◊ Includes Mounting Plate (250027760000)

Dimensions

Height: 6.9" (175 mm)
Depth: 4.0" (102 mm)
Base Diameter: 5.3" (135 mm)
Lead: 10' (3 m)
Material: Aluminum

ACCESSORIES: Specify Separately

Name	Code	Name	Code
Solite Spread (MR-16)	250015240000	Flood Lens	Δ-LEDFLENS
Hex Baffle (MR-16)	250015260000	Wide Flood Lens	Δ-LEDWFLENS



RC DESIGNER PLUS



4" Retrofit Housing

Fixture	Luxor Option	LED Configuration	Finish
RC	[blank] Zone	1LED 85 Lumens* 2.0W/2.4VA	BZ DG WI SB FB WG* FW** AL** SV**
	ZD Zone/Dim	3LED 261 Lumens* 4.2W/4.5VA	
		6LED 413 Lumens* 8.2W/9.7VA	
		9LED 722 Lumens* 10.0W/10.7VA	
	ZDC [◊] Zone/Dim/ Color	[blank] 178 Lumens* 9.1W/11.0VA	

ORDERING EXAMPLE: ▶ RC-3LED-FW = FIXTURE-LED-FINISH

Dimensions

Height: 3.5" (89 mm)
Diameter: 5.5" (140 mm)
Exposed Depth: 0.1" (3 mm)
Lead: 10' (3 m)
Material: Aluminum

ACCESSORIES: Specify Separately


Name	Code	Name	Code	Name	Code
Hex Baffle (MR-16)	250015260000	Flood Lens	Δ-LEDFLENS	4" (102 mm) Recessed Down Light Housing (Qty: 6)	CANR4RICAT
Solite Spread (MR-16)	250015240000	Wide Flood Lens	Δ-LEDWFLENS	Step-Down Transformer (12V), Universal Input Voltage (120V-233V)	ST-UV
				Step-Down Transformer, Dimmable (120V- 12V, 60W)	ST-120-DIM



Powder Coat: Standard



Powder Coat: Specialty



† Non-returnable ◊ Fixtures specified with ZDC Technology[®] are available only in one circuit board configuration. Do not specify a number of LEDs when ordering.
* May require longer lead time ** Finish code * Total delivered lumens