

BID SPECIFICATIONS
Turf Management
ZTE Spreader Sprayers
ZS4230

SPECIFICATIONS

Engine – Vanguard

Drive System – Pump & Wheel Motor

Ground Speed – 0-8.0 mph (12.9 kmph) forward, 0-4.0 mph (6.4 kmph) reverse

Drive Tires – 20 x 8.0-8

Front Caster Tires – 16 x 6.5-8

Curb Weight – 900 lbs.

Dimensions:

Width.....42 in

Length.....73 in.

Height.....50 in.

Fuel Capacity – 5-gallon (18.9-L) fuel tank

Onboard Intelligence - Digital Speedometer

Hopper Size – 150 lbs. + two 50 lbs. fertilizer trays; hydraulic motor

Spread Width – Adjustable from 3 ft. up to 25 ft.

Tank Capacity – 30 gal. (two 15 gal.)

Spray Width – 2 ft, 4 ft, 6 ft, or 8 ft

Spray Application Rate – Capacity per Nozzle - 0.22 gpm at 30 psi, 0.25 gpm at 40 psi

Pump – Remco (5.0 gpm)

Available Accessories and Attachments

Foam Marker..... 135-6663

Kit, Liquid Valve (7 GPM) and Alternator..... 135-7916

Kit-Alternator 135-7923

Mid/JR/JR36 – 7 Gallon auxiliary Tank (Left Side)..... 135-6658

Mid/JR/JR36 – 7 Gallon Isolated Tank (Right Side)..... 135-6647