

LASCO SWING JOINTS

First Digit

G

Step 1

Step 2

Step 3

-

Step 4

Step 5

Step 5

Base Part Number

Step 1 - Specify a Body Diameter by Number

Second Digit	Diameter Size
1	1"
2	1¼"
3	1½"

Step 2 - Specify an Inlet by Number

Third Digit	Inlet Size
1	Socket
2	Spigot (Short)
3	Male Thread (MIPT)
4	Male ACME
5	Metric Spigot
6	Male BSPT
7	Long Spigot (4" Long)
8	Female BSPT
9	Reducing Female BSPT
H	Spigot Saddle Connection (Increases from 1" Spigot to Swing Joint size)
M	Main Line (Reduces from 1½" ACME to Swing Joint size)
P	Tap ^t ™ Saddle Connection (Reduces from 1½" ACME to Swing Joint size)



Step 3 - Specify an Outlet by Number

Fourth Digit	Outlet Style
1	Socket
2	MIPT (Available in 1", 1¼" and 1½" diameter)
3	Enlarging MIPT (Available in 1", 1¼" and 1½" diameter)
4	MIPT Special (Available in 1" and 1¼" diameter)
5	Thread BSPT (Available in 1", 1¼" and 1½" diameter)
6	Enlarging BSPT (Available in 1½" diameter)
7	Reducing MIPT (Available in 1" diameter)
8	Increasing ACME (Available in 1½" diameter)
9	Increasing BSPT (Available in 1¼" diameter)
0	ACME (Available in 1", 1¼" and ½" diameter)
A	ACME Special (Available in 1¼" diameter)
C	Reducing ACME (Available in 1" diameter)
D	Reducing BSPT
S	SnapLok (Available in 1" and 1½" diameter)
T	Reducing SnapLok (Available in ¾" diameter)
U	BSPT SnapLok (Available in 1" diameter)

Step 4 - Swing Joint Style

Fifth Digit	Swing Joint Style
1	Kits
2	Unitized Standard Sizes
3	Fabricated Length
4	Triple Top-Out
5	Fabricated Length with Triple Top-Out

Step 5 - Specify Lay Length

Style	Last 2 Digits	Lay Length	
1__ or 4__	00	-----	Kits
2__	08	8"	Unitized Standard Sizes
	12	12"	
	18	18"	
3__	10	10"	Fabricated Sizes
	24	24"	
	30	30"	
<i>Please inquire about the availability of other lengths.</i>			
4__	08	8"	Unitized Triple Top Sizes
	12	12"	
	18	18"	
5__	10	10"	Fabricated Triple Top Sizes
	24	24"	
	30	30"	
<i>Please inquire about the availability of other lengths.</i>			

Swing Joint Carton Quantity

Part No.	Lay Length (in)	Ctn Qty
G__-_08	8"	15
G__-_12	12"	15
G__-_18	18"	10













Note: All 1" Diameter are packaged 15 to a carton. The G3__-412 are 10 per carton.

Build and price your own unit with our online Swivel Joint Configurator at
www.lascofittings.com



Swing Joint
Configurator

LASCO SWING JOINT INLETS

Inlets						
ID #	Inlet	Description	Inlet Size	Swing Joint Size	Replacement Inlet Part No.	Carton Qty
1		Socket Socket x ACME	1"	1"	G110-000	5
			1¼"	1¼"	G210-000	5
			1½"	1½"	G310-000	5
2		Spigot - Short Spigot x ACME	1"	1"	G120-000	5
			1¼"	1¼"	G220-000	5
			1½"	1½"	G320-000	5
3		MIPT MIPT x ACME	1"	1"	G130-000	5
			1¼"	1¼"	G230-000	5
			1½"	1½"	G330-000	5
4		Male ACME ACME x ACME	1"	1"	G001-006	5
			1¼"	1¼"	G001-005	5
			1½"	1½" (same as M)	G001-004	5
5		Metric Spigot Spigot x ACME	1" (2,5cm)	1"	G150-000	5
			1¼" (3,2 cm)	1¼"	G250-000	5
			1½" (4,0 cm)	1½"	G350-000	5
6		Male BSPT Male BSPT x ACME	1" (2,5cm)	1"	G160-000	5
			1¼" (3,2 cm)	1¼"	G260-000	5
			1½" (4,0 cm)	1½"	G360-000	5
7		Long Spigot 4" Long Spigot x ACME	1"	1"	G170-000	5
			1¼"	1¼"	G270-000	5
			1½"	1½"	G370-000	5
8		Female BSPT Female BSPT x ACME	1" (2,5cm)	1"	G180-000	5
			1½" (4,0 cm)	1½"	G380-000	5
9		Reducing Female BSPT Female BSPT x ACME	1½" (4,0 cm) 1½"	1" 1"	G190-000	5
H		Spigot Saddle Connection Increases from 361-211 Saddle to Swing Joint Size	1"	1"	G120-017	5
			1"	1¼"	G220-018	5
			1"	1½"	G320-019	5
M		Main Line Connection Reduces from 1½" ACME Service Fitting to Swing Joint Size	1½"	1"	G001-014	5
			1½"	1¼"	G001-016	5
			1½"	1½"	G001-004	5
P		Tap't™ Saddle Connection Reduces from 1½" ACME Tap't™ Saddle to Swing Joint Size	1½"	1"	G001-017	5
			1½"	1¼"	G001-018	5
			1½"	1½"	G001-019	5