

# PGJ

Radius: **15' to 37'**  
Flow: **0.64 to 5.3 GPM**

The highly durable PGJ offers all the benefits of a large rotor in a compact, spray-sized package, with water-efficient nozzles and easy arc adjustment.

## KEY BENEFITS

- Headed and slotted setscrew allows radius adjustment with a Hunter wrench or flat-blade screwdriver
- Adjustable arc from 40° to 360° to keep water in the appropriate areas
- Standard factory installed 2.0 nozzle speeds installation
- QuickCheck™ arc mechanism for fast arc adjustment

## OPERATING SPECIFICATIONS

- Nozzle choices: 8
- Radius: 15' to 37'
- Flow: 0.64 to 5.3 GPM
- Recommended pressure range: 30 to 50 PSI
- Operating pressure range: 20 to 100 PSI
- Precipitation rate: 0.6 in/hr approximately
- Nozzle trajectory: 14° approximately
- Warranty period: 2 years

## FACTORY-INSTALLED OPTIONS

- Drain check valve (up to 7' of elevation) excluding PGJ-00
- Reclaimed water ID

## USER-INSTALLED OPTIONS

- Drain check valve (up to 7' of elevation) excluding PGJ-00 (P/N 462078SP)
- HC-50F-50M Check valve (up to 32' of elevation) PGJ-00



### PGJ Reclaimed

Available as a factory-installed option on all models

### PGJ - SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1	Model	2	Standard Features	3	Feature Options
	PGJ-00 = Shrub	Adjustable arc, 8 standard nozzles			(blank) = No option
	PGJ-04 = 4" pop-up				V = Drain check valve
	PGJ-06 = 6" pop-up				R = Drain check valve and reclaimed water ID
	PGJ-12 = 12" pop-up				

#### Examples:

- PGJ-04 = 4" pop-up, adjustable arc
- PGJ-06-V = 6" pop-up, adjustable arc, with drain check valve
- PGJ-12-R = 12" pop-up, adjustable arc, with drain check valve and reclaimed water ID

Compatible with:



1/2" Swing Joints  
Page 62



Hunter Flex<sup>SG</sup>  
Page 26



### PGJ-00

Overall height: 7"  
Exposed diameter: 1 1/8"  
Inlet size: 1/2"

### PGJ-04

Overall height: 7 1/8"  
Pop-up height: 4"  
Exposed diameter: 1 1/8"  
Inlet size: 1/2"

### PGJ-06

Overall height: 9 1/8"  
Pop-up height: 6"  
Exposed diameter: 1 1/8"  
Inlet size: 1/2"

### PGJ-12

Overall height: 16 3/8"  
Pop-up height: 12"  
Exposed diameter: 1 1/8"  
Inlet size: 1/2"

### PGJ RED NOZZLE PERFORMANCE DATA

Nozzle	Pressure PSI	Radius ft.	Flow GPM	Precip in/hr	
				■	▲
.75 Red	30	15	0.64	0.55	0.63
	<b>40</b>	<b>16</b>	<b>0.75</b>	<b>0.56</b>	<b>0.65</b>
	50	17	0.85	0.57	0.65
1.0 Red	30	18	0.85	0.51	0.58
	<b>40</b>	<b>19</b>	<b>1.0</b>	<b>0.53</b>	<b>0.62</b>
	50	19	1.1	0.59	0.68
1.5 Red	30	21	1.3	0.57	0.66
	<b>40</b>	<b>22</b>	<b>1.5</b>	<b>0.60</b>	<b>0.69</b>
	50	22	1.7	0.68	0.78
2.0 Red	30	24	1.7	0.57	0.66
	<b>40</b>	<b>25</b>	<b>2.0</b>	<b>0.62</b>	<b>0.71</b>
	50	25	2.3	0.71	0.82
2.5 Red	30	27	2.2	0.58	0.67
	<b>40</b>	<b>28</b>	<b>2.5</b>	<b>0.61</b>	<b>0.71</b>
	50	28	2.8	0.69	0.79
3.0 Red	30	30	2.5	0.53	0.62
	<b>40</b>	<b>31</b>	<b>3.0</b>	<b>0.60</b>	<b>0.69</b>
	50	31	3.4	0.68	0.79
4.0 Red	30	33	3.7	0.65	0.76
	<b>40</b>	<b>34</b>	<b>4.0</b>	<b>0.67</b>	<b>0.77</b>
	50	34	4.3	0.72	0.83
5.0 Red	30	36	4.7	0.70	0.81
	<b>40</b>	<b>37</b>	<b>5.0</b>	<b>0.70</b>	<b>0.81</b>
	50	37	5.3	0.75	0.86

### PGJ NOZZLES



**Bold** = Recommended pressure

#### Note:

All precipitation rates calculated for 180° operation. For the precipitation rate for a 360° sprinkler, divide by 2.